



SECTION 09 29 00 – GYPSUM BOARD, 5/8 in. (15.9 mm) USG Sheetrock® Brand EcoSmart Panels Firecode® X (UL Type ULIX™)

Sustainability Notes: (Architecture 2030 Challenge for Products – LEED® v4 EPD/LCA improvements)

- USG Sheetrock® Brand EcoSmart Panels Firecode® X (UL Type ULIX™) are formulated and manufactured using the most sustainable method to date
 - Up to 21% less global warming potential (GWP)¹
 - Up to 22% less weight reduces transportation fuel energy by up to 20%
 - Living Building Challenge™ Red List Free
 - Contain 100% USDA certified biobased content
 - Up to 94.6% recycled content (regionally available)
 - Achieved GREENGUARD Gold Certification and qualify as a low VOC emitting material (meets CA 01350)
 - USGBC® LEED® v4 – may assist in achieving additional credits
- Developed to meet the Architecture 2030 Challenge for Products, USG Sheetrock® Brand EcoSmart Panels Firecode® X (UL Type ULIX™) have lower carbon dioxide emissions than standard Type X gypsum board. These values are defined by the Gypsum Association’s Type III EPD per ISO 14040 for North American Type X gypsum board.

Gypsum Panel	CO ₂ eq. (kg CO ₂ /1000 sq. ft.)
USG Sheetrock® Brand EcoSmart Panels Firecode® X (per EPD 216)	219
GA Industry Average – Standard 5/8 in. (15.9 mm) Type X	277

1. Compared to standard 5/8 in. (15.9 mm) Type X gypsum panels as presented in the Gypsum Association’s *5/8 in. (15.9 mm) Type X Conventional Gypsum Board Environmental Product Declaration (EPD 10270)*.

Product Summary:

- Sustainable and ultralightweight 5/8 in. (15.9 mm) enhanced proprietary Type X panels for interior wall and ceiling applications
- Formulated to achieve all of the same strength and performance characteristics as standard 5/8 in. (15.9 mm) USG Sheetrock® Brand Firecode® X Panels at a lower environmental impact and reduced weight
- Feature an innovative noncombustible gypsum core that is encased in 100% recycled face and back papers that form a high strength-to-weight ratio composite design
- Comply with ASTM C1396, *Standard Specification for Gypsum Board*, for 5/8 in. (15.9 mm) and Type X gypsum wallboard
- Underwriters Laboratories Inc. (UL) Classification as to fire resistance, surface-burning characteristics and noncombustibility
- Offer comparable sound, strength and sag resistance to standard 5/8 in. (15.9 mm) Type X
- Can be used in any UL Design in which UltraLight Innovation Type X (ULIX™) panels are listed
- For more information, refer to product submittal sheet WB2859 or usg.com

Note to Specification Writers:

- This document is not intended to function as a standalone specification. It is intended to assist the specifier in inserting the proper language into the following recommended specification sections: 09 29 00 – GYPSUM BOARD.
- This product is manufactured at USG gypsum panel plants, reducing distances and carbon footprint for transport.
- Panels shall be installed in accordance with GA-216, *Specifications for the Application and Finishing of Gypsum Panel Products* and ASTM C840, *Standard Specification for Application and Finishing of Gypsum Board*.
- Contact USG at 800.874.4968 for technical questions.

PART 2 – GYPSUM PANEL PRODUCTS

2.1 SUSTAINABLE TYPE X GYPSUM PANEL

- A. ASTM C1396, *Standard Specification for Gypsum Board*, for 5/8 in. (15.9 mm) and Type X gypsum wallboard
1. Basis of Design: Subject to compliance with project requirements, the design is based on the following: United States Gypsum Company, USG Sheetrock® Brand EcoSmart Panels Firecode® X
 2. ISO 14040 Environmental Management, Life Cycle Assessment, Principles and Framework:
 - a. Carbon emissions per Gypsum Association; Industry Standard Type III EPD for North American Type X wallboard have a Global Warming Potential value of 277 kg CO₂ eq./1000 sq. ft.: **219 kg CO₂ eq./1000 sq. ft.**
 - b. Primary energy from non-renewable resources per Gypsum Association; Industry Standard Type III EPD for North American Type X wallboard have a value of 4,100 MJ/1000 sq. ft.: **3,840 MJ/1000 sq. ft.**
 3. UL Type Designation: “ULIX™”
 4. ASTM E136 Noncombustibility: Meets
 5. ASTM E84 Surface-Burning Characteristics
 - a. Flame Spread: 5
 - b. Smoke Developed: 5
 - c. Class A (Flame spread not greater than 25 and smoke developed not greater than 450): Meets
 6. ASTM C473, *Standard Test Methods for Physical Testing of Gypsum Panel Products*
 - a. Core Hardness
 - 1) Field [Not less than 11 lbf (49 N)]: Meets
 - 2) End [Not less than 11 lbf (49 N)]: Meets
 - 3) Edge [Not less than 11 lbf (49 N)]: Meets
 - b. Flexural Strength
 - 1) Parallel [Not less than 46 lbf (205 N)]: Meets
 - 2) Perpendicular [Not less than 147 lbf (654 N)]: Meets
 - c. Nail Pull Resistance [Not less than 87 lbf (387 N)]: Meets
 - d. Humidified Deflection [Not greater than 5/8 in. (15.9 mm)]: Meets
 7. Thickness: 5/8 in. (15.9 mm)
 8. Length: 8-16 ft. (2438-4877 mm)
 9. Width: 4 ft. (1219 mm), 54 in. (1372 mm)
 10. Weight: 1.8 lb./sq. ft. (8.8 kg/sq. m.)
 11. Edge: Tapered

Disclaimer: The USG Product Specifications contained herein are intended for use as product reference material by architects, engineers, other design professionals, contractors, building code officials, or other competent construction industry trade professionals having an interest in the selection, specification and use of products manufactured by the subsidiaries of USG Corporation. The specifications are intended solely as technical support incident to the sale and use of USG products and not intended to be a substitute for the design review and approval of the licensed design professionals for the project. These materials may be printed and/or transferred electronically solely as needed by the user. Because electronic files can be modified by other parties, without notice or indication of such modifications, modification of USG Product Guide Specifications is the sole responsibility of the Design Professional.