

HPD UNIQUE IDENTIFIER: 916136022016

CLASSIFICATION: 09 20 00 Plaster and Gypsum Board

PRODUCT DESCRIPTION: USG Sheetrock® Brand Firecode® X Gypsum Panels are composed of fire-resistant gypsum core encased in 100-percent recycled natural-finish face paper and 100-percent recycled liner paper on the back. These panels score and snap easily for quick installation of interior wall and ceiling applications, allowing painting, decorating and the installation of metal or wood almost immediately.

Section 1: Summary

Basic Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities Evaluation	<i>For all contents above the threshold, the manufacturer has:</i>
☐ Nested Materials Method	☒ 100 ppm	☒ Completed	Characterized ☒ Yes ☐ No
☒ Basic Method	☐ 1,000 ppm	☐ Partially Completed	<i>Provided weight and role.</i>
Threshold Disclosed Per	☐ Per GHS SDS	☐ Not Completed	Screened ☐ Yes ☒ No
☐ Material	☐ Other	Explanation(s) provided :	<i>Provided screening results using HPDC-approved methods.</i>
☒ Product		☒ Yes ☐ No	Identified ☐ Yes ☒ No
			<i>Provided name and CAS RN or other identifier.</i>

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

PRODUCT | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

SHEETROCK® BRAND FIRECODE® X PANELS [GYPSUM BM-3dg]

MAM CELLULOSE, MICROCRYSTALLINE [LT-UNK] RES STARCH

NoGS SOLID GLASS AND GLASS / MINERAL FIBER (SEE VARIANTS)

[LT-UNK] METAPHOSPHORIC ACID (H3P3O9), TRISODIUM SALT [LT-UNK]

[UNK] NAPHTHALENESULFONIC ACID, FORMALDEHYDE POLYMER, CALCIUM SALT [LT-P1] POLYVINYL ACETATE (PVA) [LT-UNK]]

Number of Greenscreen BM-4/BM3 contents ... 1

Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... LT-P1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

Residuals/Impurities in raw materials that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS are displayed in the HPD when greater than or equal to 1000 ppm. USG uses an outside lab to quantify potential impurities of raw materials. Analytical methods may include but are not limited to; x-ray diffraction, x-ray fluorescence, atomic absorption, ion chromatography, liquid chromatography, and crystalline silica analysis.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: UL/GreenGuard Gold Certified

CONSISTENCY WITH OTHER PROGRAMS

No pre-checks completed or disclosed.

Third Party Verified?	PREPARER: Self-Prepared	SCREENING DATE: 2024-05-23
☐ Yes	VERIFIER:	PUBLISHED DATE: 2024-05-23
☒ No	VERIFICATION #:	EXPIRY DATE: 2027-05-23

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

SHEETROCK® BRAND FIRECODE® X PANELS

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

RESIDUALS AND IMPURITIES NOTES: Raw materials in this product may contain trace amounts of respirable crystalline silica. Testing has shown exposures to respirable crystalline silica are not expected to exceed the OSHA Permissible Exposure Level (PEL) during the normal use of this product. See the SDS on usg.com for occupational exposure information. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

OTHER PRODUCT NOTES: This product is made at Aliquippa, PA, Baltimore, MD, Bridgeport, AL, East Chicago, IN, Galena Park, TX, Hagersville, ON, Jacksonville, FL, Montreal, QC, Norfolk, VA, Plaster City, CA, Rainier, OR, Saint John, NB, Shoals, IN, Sigurd, UT, Sperry, IA, Sweetwater, TX, and Washingtonville, PA. Percent ranges displayed for this HPD are for all manufacturing plants that make this product and may vary.

GYPSUM

ID: 13397-24-5

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2024-05-23 10:35:24		
%: 90.0000 - 95.0000	GreenScreen: BM-3dg	RC: PreC	NANO: No	SUBSTANCE ROLE: Structure component	
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS		
MAM	GHS - Japan		H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION		
None found			No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. This product contains 94.6% PreC recycled content. The use of FGD gypsum and the pre-consumer recycled content of Sheetrock® Brand Firecode® X Panels will vary by the manufacturing plant.					

CELLULOSE, MICROCRYSTALLINE

ID: 9004-34-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2024-05-23 10:35:24		
%: 3.0000 - 7.0000	GreenScreen: LT-UNK	RC: PostC	NANO: No	SUBSTANCE ROLE: Structure component	
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS		
RES	AOEC - Asthmagens		Asthmagen (Rs) - sensitizer-induced		

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
EXEMPT	European Union / European Commission (EU EC)	EU - REACH Exemptions Exempted from REACH Annex IV listing due to intrinsic safety
SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. This product contains 3.4% PostC recycled content.		

STARCH

ID: 9005-25-8

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2024-05-23 10:35:25		
%: 0.1000 - 0.5000	GreenScreen: NoGS	RC: None	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
None found			No warnings found on HPD Priority Hazard Lists	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
EXEMPT	European Union / European Commission (EU EC)		EU - REACH Exemptions	
			Exempted from REACH Annex IV listing due to intrinsic safety	
SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.				

SOLID GLASS AND GLASS / MINERAL FIBER (SEE VARIANTS)

ID: 65997-17-3

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2024-05-23 10:35:25		
%: 0.1000 - 0.5000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Tensile strength additive
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
	EC - CEPA DSL	Persistent		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
EXEMPT	European Union / European Commission (EU EC)	EU - REACH Exemptions Exempted from REACH Annex V listing due to intrinsic safety		

SUBSTANCE NOTES: As manufactured, continuous filament glass fibers in this product are not respirable. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

METAPHOSPHORIC ACID (H3P3O9), TRISODIUM SALT

ID: 7785-84-4

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2024-05-23 10:35:25		
%: 0.0100 - 0.2000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Tensile strength additive	
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS		
	EC - CEPA DSL		Persistent		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION		
None found			No listings found on Additional Hazard Lists		

SUBSTANCE NOTES: Proprietary ingredient. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS. Not on the Living Future - Living Building Red List - Red List substances to avoid in Living Building Challenge v3 projects.

NAPHTHALENESULFONIC ACID, FORMALDEHYDE POLYMER, CALCIUM SALT

ID: 37293-74-6

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2024-05-23 10:35:26	
%: 0.0100 - 0.0700	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Dispersant
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
	EC - CEPA DSL		Persistent	
	EC - CEPA DSL		Bioaccumulative	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
RESTRICTED LIST	International Living Future Institute (ILFI)		Living Building Challenge 4.0 - Red List of Materials & Chemicals - Effective April 1, 2024	
			Red List substances to avoid in Living Building Challenge V4.0 projects	

SUBSTANCE NOTES: USG has made an effort to decrease and will ultimately replace this dispersant. No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

POLYVINYL ACETATE (PVA)

ID: 9003-20-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2024-05-23 10:35:26		
%: 0.0100 - 0.0500	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Adhesive	

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
	EC - CEPA DSL	Persistent
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: No Residuals or Impurities are expected to be present at or above the 1000 ppm threshold that return a GreenScreen® score of BM-1, LT-1, LT-P1 or NoGS.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	UL/GreenGuard Gold Certified	
CERTIFYING PARTY: Third Party	ISSUE DATE: 2016-01-29 00:00:00	CERTIFIER OR LAB: UL
APPLICABLE FACILITIES: All	EXPIRY DATE:	Environment
CERTIFICATE URL: https://spot.ul.com/		
CERTIFICATION AND COMPLIANCE NOTES: Building products and interior finishes are determined compliant in accordance with California Department of Public Health (CDPH) Standard Method V1.2-2017 using an Office and Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2. Maximum allowable predicted TVOC concentrations for GREENGUARD Gold (0.22 mg/m ³) fall in the range of 0.5 mg/m ³ or less, as specified in CDPH Standard Method v1.2.		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

USG SHEETROCK® OR BEADEX® BRAND FINISHING PRODUCTS

MANUFACTURER (OR GENERIC): **USG**

HPD URL: <https://www.usg.com>
ACCESSORY TYPE: Other
CONDITION WHEN RECOMMENDED OR REQUIRED AND/OR OTHER NOTES: For high-quality finishing results, USG recommends USG Sheetrock® or Beadex® Brand finishing products. Painting products and systems should be used that comply with recommendations and requirements in Appendices of ASTM C840. For priming and decorating with paint, texture or wall covering, follow manufacturer's directions for materials used. Gypsum Association's Recommended Specification for Levels of Gypsum Board Finish (GA-214) should be referred to in order to determine the level of finishing needed to ensure a surface properly prepared to accept the final decoration. For additional installation information, refer to product submittal sheet.

Section 5: General Notes

The International Agency for Research on Cancer (IARC) in June, 1987, categorized continuous filament glass fibers as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify continuous filament glass fiber as a possible, probable, or confirmed cancer causing material.

MANUFACTURER INFORMATION

MANUFACTURER: **USG**
ADDRESS: **550 West Adams St**
Chicago, IL 60661
COUNTRY: **United States**

WEBSITE: **usg.com**
CONTACT NAME: **Stacy Simpson**
TITLE: **Sustainability Manager**
PHONE: **1-800-USG4YOU**
EMAIL: **sustainability@usg.com**

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold	Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold	Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold	Substances listed individually per threshold indicated per product

Nano	Composed of nano scale particles or nanotechnology
Third Party Verified	Verification by independent certifier approved by HPDC
Preparer	Third party preparer, if not self-prepared by manufacturer
Applicable facilities	Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,*
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and

