

SHEETROCK® Wall and Ceiling Texture Paint



**Interior White Latex
Spray, Brush, or Roller Applied**



Provides a fine, light sand finish to interior walls and ceilings

- Dries to a hard, durable, natural white finish.
- Conceals minor surface defects.
- Applies quickly and easily.



Fine Sand

Description	Formulated to provide a fine, uniform texture over interior surfaces of gypsum drywall, plaster, concrete, wood, and other materials. Swirl patterns and other designs may be created by using a paint brush or texturing brush. Gives a durable, natural white finish.	
Advantages	<p><i>Classic texture.</i> Subtle, versatile light sand finish.</p> <p><i>Easy to use.</i> Applies with spray, roller or brush.</p> <p><i>Economical.</i> Fast, low-cost application with coverage up to 200 sq. ft. per gallon.</p>	
Limitations	<ol style="list-style-type: none"> 1. During application, avoid drafts and maintain minimum temperature of 55 °F within working areas. 2. Use fresh material. Store in a dry location at room temperature. Protect from freezing. 3. Do not exceed recommended water proportions. 4. Do not intermix. 	
Directions	Surface Preparation	<p>Substrate must be sound, dry, clean, and free of oil, grease, mildew, efflorescence, and other foreign materials and/or contaminants. Product, air, and surface temperatures must be maintained at a minimum of 55 °F (13 °C) throughout the finishing process when using joint compound, primer, and texture products.</p> <p><i>New Drywall</i> <i>New Concrete/Plaster</i> Treat joints and nailheads with an appropriate USG Joint Treatment System. Age at least 60 days before texturing. Remove form oils and efflorescence and grind down form lines. Fill cracks and holes, and level concrete surfaces with SHEETROCK® Setting-Type (DURABOND®) or Lightweight Setting-Type (EASY SAND™) Joint Compound or COVER COAT® Compound and let dry.</p> <p><i>Painted Surfaces</i> Lightly sand to dull any sheen and develop “tooth” for good bond. Wash surface with a strong detergent from the bottom up to remove any dust, dirt, or sheen. A strong solution of TSP (trisodiumphosphate) works best. Follow manufacturer’s directions on the container.</p> <p>Note: Texturing over previously painted, textured, or stained substrates may require application(s) of a stain-blocking sealer to obtain uniform color (check manufacturer’s instructions for stain containment instructions). Prevent rust stains by spot-priming bare metal with a good rust-inhibitive primer and let dry prior to the full surface priming.</p>
	Substrate Priming	Application of a prime coat is necessary to equalize surface porosity. After prepared surfaces have thoroughly dried, apply a prime coat of SHEETROCK® First Coat flat latex paint or a good quality interior latex flat wall paint with high solids content. Prime coat should be applied undiluted and allowed to dry before decorating.
	Mixing	If necessary, adjust consistency by slowly adding water, maximum 1 pint per gallon of product. Avoid overthinning. Mix until consistency is smooth and uniform. Note: Overthinning may cause poor adhesion, lack of hide, and unequal suction when dry. Do not intermix with paints or other materials.
	Application	Apply TEXOLITE Sanded Paste Stipple when air, water, mix, and surface temperatures are above 55 °F. Using a roller or brush, apply generously in long strokes. Cross-roll adjoining areas to prevent ridging and framing. Note: Avoid drafts during application; provide ventilation when work is complete.
	Drying Time	At 72 °F, 50% relative humidity, allow 2 to 4 hours. Wait overnight before overcoating.

Coverage	Five gallons covers up to approximately 1,000 sq. ft. (93 sq. m) based on use over smooth, hard surfaces. Masonry, textured, rough, and porous surfaces will require more product.
Cleanup	Clean hands and equipment with warm, soapy water before texture hardens.

Product Data	Color:	White. May be painted after drying.
	Dilution (water):	Up to 1 pint per gallon.
	pH:	9.2 to 9.5.
	Drying Time:	At 72 °F, 50% relative humidity, dries in 2-4 hours.
	Coverage:	Up to 200 sq. ft. per gal.
	Storage:	Close container after each use. Store in dry place at room temperature. Protect from freezing. Rotate stock on a first-in, first-out basis.
	Shelf Life:	Up to 9 months shelf life under good storage conditions.
	Packaging:	1 and 5 gallon pails.
	Coating VOC:	6 g/L.
	Material VOC:	2 g/L.
VOS:	Maximum of 0.075 lbs./gallon.	

Submittal Approvals:	Job Name	
	Contractor	Date

WARNING

Spraying mist or dust created from product may cause eye, skin, nose, throat, or respiratory irritation. Avoid inhalation of mist or dust. Wear a NIOSH/MSHA-approved respirator when dusty or misty or if spray applying. Use proper ventilation to reduce mist/dust exposure. Wear eye protection. If eye contact occurs, immediately flush thoroughly with water for 15 minutes. If irritation persists, call physician. Wear long-sleeved work clothing to prevent skin irritation. Wash thoroughly with soap and water after use. Do not ingest. If ingested, call physician. Product safety information: (800) 507-8899. KEEP OUT OF REACH OF CHILDREN.

Trademarks:

The following trademarks used herein are owned by United States Gypsum Company: COVER COAT, DURABOND, EASY SAND, SHEETROCK.

Note:

Products described here may not be available in all geographic markets. Consult your U.S. Gypsum Company sales office or representative for information.

Notice:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.