

PLUS²

USC

AN UNRIVALED FINISH. EVERY TIME.

IISG SHEETROCK

USG SHEETROCK[®] BRAND INTERIOR FINISHING PRODUCTS

usg.com





At USG, we know that settling for "good enough" is never an option. You need reliable, high-quality products that you can depend on every time.

For more than 100 years, USG has been the leading manufacturer of the highest-performing building materials within the industry. So you can trust that when you choose our products, you're always getting the best possible quality.

We offer finishing products specifically designed to meet your needs, and a full portfolio that provides unique and adaptable solutions for a variety of environments.

Beyond outstanding products, we also offer expertise, technical support and nationwide availability. All driven by a dedication to finding solutions for you. Plus, we have the technology and manufacturing capabilities to ensure our products exceed industry standards before ever being used.

TABLE OF CONTENTS

Finishing Solutions 7 Joint Compounds 13 Joint Tapes **15** Bead and Trim **Surfacing Solutions 25** Interior Textures Plaster 27 **31** Plaster Accessories **Preparation Solutions** 33 Primers Sealants **Interior Patch & Repair Solutions 36** Repair Products 37 USG Commodity Codes



AUBURN. W DENVER, CO SIGURD, UT TORRANCE, CA PHOENIX, AZ

Whether you prefer a lightweight, conventional weight, or airborne dust reducing joint compound, USG has a solution specifically formulated to meet your needs – wherever you are.

For more than 100 years, our customers have relied on USG to develop and deliver high-performing products. With nearly 200 years of combined formulation experience – and a manufacturing network that spans the country – USG Sheetrock[®] Brand Joint Compounds provide you with the largest portfolio in the industry, all backed by nationwide distribution.

USG MANUFACTURING LOCATIONS

Dallas, TX

* **REGIONS**



Auburn, WA Baltimore, MD Bridgeport, AL Cartersville, GA Denver, CO East Chicago, IN Fort Dodge, IA Galena Park, TX

////// West East

* For Bead and Trim products

Gypsum, OH Jacksonville, FL Phoenix, AZ Port Reading, NJ Shoals, IN Sigurd, UT Torrance, CA Weirton, WV



JOINT COMPOUNDS

READY-MIX JOINT COMPOUNDS

USG ready-mixed joint compounds are preferred for consistently high-quality work. Superior formulations are premixed to a creamy, smooth consistency and are essentially free of crater-causing air bubbles. USG ready-mixed joint compounds can be used in hand or machine-tool applications and offer excellent slip, bond, and easy workability.

Most USG joint compound products are GREENGUARD GOLD certified. Please review product data available at usg.com or usg.ecomedes.com for product specific compliance.

CONVENTIONAL WEIGHT

USG SHEETROCK[®] BRAND ALL PURPOSE JOINT COMPOUND



- Combines single-package convenience with good taping and finishing performance
- Recommended for skim coating and for laminating and repairing cracks in interior plaster and masonry not subject to moisture
- Great open time and cold bond
- Smooth and slick properties

USG SHEETROCK[®] BRAND TOTAL[™] JOINT COMPOUND



- conventional-weight compounds • Offers excellent bond over bead, trim and fastener concealments
- Special formulation is ideal for embedding tape and for filling, leveling and finishing over gypsum panel joints, fasteners, bead and trim

USG SHEETROCK[®] BRAND TAPING JOINT COMPOUND



- Ideal for patching plaster cracks and for use on most gypsum board when maximum bond and crack resistance are essential
 - Best ready-mixed compound for laminating and is ideal for use in most major tools

USG SHEETROCK[®] BRAND TOPPING JOINT COMPOUND



- - Easily applied and sanded
 - Recommended for second and third coats
 - Note: Do not use to embed joint tape, to skim coat, or fill metal bead and trim

FINISHING SOLUTIONS

Offering the industry's broadest selection of finishing solutions, our high-quality joint compounds, joint tapes, beads and trims deliver superior performance for every job, every time. Whether you're taping, applying a finish coat or patching a crack, there is a USG finishing product to meet your needs.





PRODUCT DATA

AVAILABLE IN: 1.75 pt. tub, 3.5 qt. pail, 4.5 gal. pail, 3.5 gal. carton, 4.5 gal. carton*

PRODUCT DATA

• Smoother working and sands more easily than most other

REGIONAL AVAILABILITY: Phoenix / Sigurd / Torrance

AVAILABLE IN: 3.5 gal. carton

• High-performance compound for embedding tape

PRODUCT DATA

REGIONAL AVAILABILITY: Auburn / Torrance

AVAILABLE IN: 3.5 gal. carton

PRODUCT DATA

• Excellent finishing compound with superior crater resistance

REGIONAL AVAILABILITY: Auburn / East Chicago / Fort Dodge / Gypsum / Phoenix / Sigurd / Torrance

AVAILABLE IN: 4.5 gal. pail, 3.5 gal. carton

* Packaging size availability may vary by market.

CONVENTIONAL WEIGHT CONT.

USG BEADEX[®] BRAND ALL PURPOSE JOINT COMPOUND



- Combines single-package convenience with good taping and topping performance
- Ideal for embedding and finishing, hand-applied simple texturing, skim coating, laminating and repairing cracks in interior plaster and masonry not subject to moisture

USG BEADEX[®] BRAND TAPING JOINT COMPOUND



Best ready-mixed compound for laminating

• High-performance compound for embedding tape

• Recommended for skim coating on most gypsum board where maximum bond is essential

USG BEADEX® BRAND TOPPING JOINT COMPOUND



- Excellent finishing compound with superior crater resistance
- Recommended for second and third coats over USG Beadex® Brand Taping and All Purpose Compounds
- Note: Do not use to embed joint tape or for the first coat over metal beads and trim

MIDWEIGHT

USG SHEETROCK[®] BRAND MIDWEIGHT[™] JOINT COMPOUND



TOTAL

- Provides superior working and sanding properties along with lower shrinkage for improved metal bead, trim, and fastener concealment
- Weighs up to 15% less than conventional-weight compounds
- Special formulation makes it ideal for embedding tape and for filling, leveling and finishing over gypsum panel joints
- Excellent for skim coating and hand-applying simple textures

USG SHEETROCK[®] BRAND TOTAL[™] LITE JOINT COMPOUND

PRODUCT DATA

Sigurd / Torrance

AVAILABLE IN:

3.5 gal. carton

REGIONAL AVAILABILITY:

PRODUCT DATA

Auburn

Auburn

Auburn

AVAILABLE IN:

3.5 gal. carton

PRODUCT DATA

4.5 gal. pail, 3.5 gal. carton,

AVAILABLE IN:

4.5 gal. carton*

AVAILABLE IN:

3.5 gal. carton

PRODUCT DATA

REGIONAL AVAILABILITY:

AVAILABLE IN:

RODUCT DATA

REGIONAL AVAILABILITY:

REGIONAL AVAILABILITY:

4.5 gal. pail, 3.5 gal. carton

- Superior working qualities and good open time facilitates working back under fast drying conditions
- Weighs up to 15% less than conventional-weight compounds
- Easier working and sanding, and provides lower shrinkage for bead, trim and fastener concealments
- Special formulation makes it ideal for embedding paper tape and for filling, leveling and finishing over gypsum panel joints, fasteners, bead and trim

* Packaging size availability may vary by market.

LIGHTWEIGHT

USG SHEETROCK[®] BRAND PLUS 3[®] JOINT COMPOUND



- · Features good open time and less shrinkage
- Requires one fewer coat over fasteners and bead, eliminating the need for taping and topping compounds
- Sands with the ease of a topping compound and bonds like a taping compound

USG SHEETROCK[®] BRAND DUST CONTROL JOINT COMPOUND

- Unique formula binds up fine residue during sanding to form heavier particles that tend to fall to the floor instead of clouding the air
- Requires only two coats over bead and fasteners
- Bonds like a taping product for a tough, tight bond under most job conditions
- · Combines all-purpose, single-package convenience with optimum taping and topping performance

USG SHEETROCK[®] BRAND TAPING LITE JOINT COMPOUND

- ISG SHEETROCK **TAPING** LITE
- For use in mechanical taping tools, as well as on most gypsum board when maximum bond and crack resistance are essential • Ultralightweight formulation is designed for mechanical tools and is less fatiguing for overhead applications
- Superior slip and adhesion
- · Ideal for embedding paper joint tape

USG SHEETROCK® BRAND TOPPING LITE JOINT COMPOUND



ELITE FINISH

- Provides increased crack resistance and is easier to sand • High-performance formulation makes it ideal for filling, leveling
- and finishing coats
- Note: Do not use to embed joint tape, to skim coat or as a texture

USG SHEETROCK[®] BRAND ELITE FINISH JOINT COMPOUND

- USG's latest premium, lightweight fill and finish compound
 - Weighs up to 40% less than conventional-weight compounds
- Softer sanding and improved open time with a creamier flow and high slip
- Note: Do not use to embed joint tape

* Packaging size availability may vary by market.

• Weighs up to 40% less than conventional-weight taping compounds

PRODUCT DATA

AVAILABLE IN: 3.5 qt. pail, 4.5 gal. pail, 3.5 gal. carton, 4.5 gal. carton*

PRODUCT DATA

AVAILABLE IN: 1 gt. patch and repair tub, 3.5 gt. pail, 3.5 gal. pail, 3.5 gal. carton*

PRODUCT DATA

REGIONAL AVAILABILITY: East Chicago / Fort Dodge / Sigurd

AVAILABLE IN: 4.5 gal. pail, 3.5 gal. carton, 4.5 gal. carton*

PRODUCT DATA

REGIONAL AVAILABILITY: Sigurd / Torrance

AVAILABLE IN: 3.5 gal. carton

PRODUCT DATA

REGIONAL AVAILABILITY: East Chicago / Fort Dodge

AVAILABLE IN: 4.5 gal. carton, 3.5 gal. carton

• Weighs up to 25% less than conventional-weight compounds

• Weighs up to 25% less than conventional-weight compounds

LIGHTWEIGHT CONT.

USG BEADEX® BRAN	PRODUCT DATA	
	 Weighs up to 30% less than conventional-weight compounds Facilitates working back, even under fast-drying conditions, by providing more wet-edge life to prevent rolling and tearing of previously laid compound Factory-controlled shrinkage results in finer finished work, but 	REGIONAL AVAILABILITY: Auburn AVAILABLE IN: 3.5 gal. carton

without the extra labor

USG BEADEX® BRAND ALL PURPOSE LITE JOINT COMPOUND



Auburn / Phoenix AVAILABLE IN:

3.5 gal. carton

PRODUCT DATA

Auburn

AVAILABLE IN:

3.5 gal. carton

REGIONAL AVAILABILITY:

REGIONAL AVAILABILITY:

3.5 qt. pail, 4.5 gal. pail,



- Combines all-purpose, single-package convenience with optimum taping and topping performance Recommended for use as an embedding and finishing compound,
- bonds like a taping product, and provides a tough, tight bond under most job conditions

USG BEADEX[®] BRAND TOPPING LITE JOINT COMPOUND



Recommended for second and third coats over USG Beadex® Brand Taping Lite and All Purpose Lite Joint Compounds

• Excellent finishing compound with superior crater resistance

• Note: Do not use to embed joint tape, to skim coat or as a texture

USG BEADEX[®] BRAND TAPING LITE JOINT COMPOUND



• Best ready-mixed compound for laminating • Ideal for skim coating on most gypsum board where maximum bond is essential

• Lightweight high-performance compound for embedding tape

USG SOQUETE® JOINT COMPOUND



Economical and well-balanced compound

- Weighs up to 15% less than conventional-weight compounds, making handling and applying easier and faster
- Provides low shrinkage for metal bead, trim and fastener concealments
- Ideal for first coat over metal, finishing, skim coating and simple hand-applied texturing

* Packaging size availability may vary by market.

ULTRALIGHTWEIGHT

USG SHEETROCK[®] BRAND ULTRALIGHTWEIGHT JOINT COMPOUND



- Weighs up to 40% less than conventional-weight compounds
- Superior formulation provides enhanced working properties and improved slip for easy application
- Provides excellent taping performance and tough finished surface, yet is easy to sand
- Great for use in mechanical tools

DRYING-TYPE JOINT COMPOUNDS

USG drying-type joint compounds are high-quality compounds that provide easy mixing, smooth application and ample working time. These compounds are ideal for embedding tape, fill coats and finishing over drywall joints, corner bead, trim and fasteners.

USG SHEETROCK[®] BRAND ALL PURPOSE JOINT COMPOUND

· All-around performer for drywall finish ISG SHEE ALL Good taping and topping in one production • Also ideal for texturing

USG SHEETROCK[®] BRAND A/P LITE[®] JOINT COMPOUND



• Lower shrinkage, better crack resistance Easier mixing, application and sanding

REGIONAL AVAILABILITY: Auburn AVAILABLE IN: 3.5 gal. carton

PRODUCT DATA

REGIONAL AVAILABILITY: Dallas / Galena Park /

Phoenix / Torrance

PRODUCT DATA

AVAILABLE IN: 3.5 gal. carton

PRODUCT DATA

AVAILABLE IN: 4.5 gal. pail, 3.5 gal. carton, 4.5 gal. carton*

n	g	
t		

PRODUCT DATA

REGIONAL AVAILABILITY: Dallas / Gypsum / Phoenix / Sigurd

AVAILABLE IN: 25 lb. bag

PRODUCT DATA

• Weighs up to 20% less than conventional-weight compounds

REGIONAL AVAILABILITY: Jacksonville / Phoenix

AVAILABLE IN: 20 lb. bag

* Packaging size availability may vary by market

SETTING-TYPE JOINT COMPOUNDS

USG setting-type joint compounds provide faster finishing of drywall interiors, even under slow drying conditions. Rapid chemical hardening and low shrinkage permit same-day finishing and usually next-day decoration. These products feature exceptional bond; virtually unaffected by humidity extremes. They are ideal for laminating double-layer systems, particularly fire-rated assemblies, and for adhering gypsum panels to above-grade concrete surfaces. May also be used for surface texturing and for filling, smoothing and finishing interior above-grade concrete. Note that setting-type joint compounds should not be used for skim coating due to dryout concerns.

USG SHEETROCK[®] BRAND EASY SAND[™] JOINT COMPOUND

PRODUCT DATA

5-, 20-, 45-, 90- and 210-minute

3 lb. resealable bag (Only 5- and 90-minute working time)

AVAILABLE IN:

working times;

PRODUCT DATA

20-, 45-, 90- and 210-minute

AVAILABLE IN:

working times;

PRODUCT DATA

Auburn

18 lb. bag

AVAILABLE IN:

working times;

REGIONAL AVAILABILITY:

5-, 20-, 40- and 90-minute

25 lb. bag

18 lb. bag

- For one-day patching and joint finishing and next-day decoration Weighs up to 25% less than conventional setting-type compounds • Easy to sand
- Provides low shrinkage and a superior bond
- Ideal for laminating drywall and patching plaster surfaces

USG SHEETROCK[®] BRAND DURABOND[®] JOINT COMPOUND



- Exceptional bond with low shrinkage Same-day finishing and next-day decorating possible Excellent check-crack resistance in heavy fills
- Unique resistance to humidity

USG BEADEX[®] BRAND SILVER SET[™] JOINT COMPOUND

- Weighs up to 28% less than conventional setting-type compounds
- Ideal for heavy fills and virtually unaffected by humidity
- Low shrinkage and superior bond, which make it excellent for laminating gypsum panels to sound-deadening boards and to above-grade concrete surfaces
- Can also be used for filling, smoothing and finishing interior concrete ceilings and above-grade concrete; taping and finishing gypsum panels, under tile and for finishing joints in exterior gypsum ceiling boards

CONCRETE FINISHING COMPOUNDS

USG SHEETROCK[®] BRAND COVER COAT[®] JOINT COMPOUND



- For filling and smoothing monolithic concrete ceilings and columns located above grade
- Easily applied—no extra bonding agent needed
- Dries to a fine white decorative surface
- Also ideal for drywall tape embedding and first coat over bead

* Packaging size availability may vary by market.

PRODUCT DATA

REGIONAL AVAILABILITY: Baltimore / Port Reading / East Chicago / Jacksonville

AVAILABLE IN: 4.5 gal. pail, 4.5 gal. carton*

JOINT TAPES

PAPER JOINT TAPES

From the originator of modern joint finishing, USG reinforcing tapes add strength and crack resistance for smooth concealment at flat joints and inside corners. USG joint tapes are high quality, easily applied, and available for specialized uses.

USG Sheetrock® Brand Joint Paper Tape is manufactured with a unique, strong, cross-fibered tape for use with USG joint compounds in reinforcing joints and corners in gypsum panels. Paper joint tape is ideal with both drying- and setting-type compounds, as it reinforces the joint compound in compression, bending and shear, and will prevent visible cracking.

All Sheetrock® Brand Joint Tape products are available in the East Region. All Beadex® Brand Joint Tape products are available in the West Region. Please refer back to page 5 for regional details.

USG SHEETROCK[®] BRAND PAPER JOINT TAPE

- Superior center creasing for trouble-free corner finishing
- High strength to resist tearing, stretching or wrinkling
- Processed for superior bond
- Wafer thin for easy joint treatment
- Meets ASTM C475, Type I

USG SHEETROCK[®] BRAND HEAVY JOINT TAPE



- Superior center creasing for trouble-free corner finishing
- High strength to resist tearing, stretching or wrinkling
- Higher cross direction strength
- Meets ASTM C475, Type II

USG BEADEX[®] BRAND DRYWALL JOINT TAPE



- High strength to resist tearing, stretching or wrinkling Processed for superior bond
 - Wafer thin for easy joint treatment
 - Meets ASTM C475, Type I



AVAILABLE IN:

PRODUCT DATA

75' roll, 250' roll, 500' roll; 2-1/16" wide

PRODUCT DATA

AVAILABLE IN: 250' roll, 500' roll; 2-1/16" wide

PRODUCT DATA

• Superior center creasing for trouble-free corner finishing

AVAILABLE IN: 75' roll, 250' roll, 500' roll; 2-1/16" wide

13

FIBERGLASS JOINT TAPES

USG Sheetrock® Brand Fiberglass Joint Tape is made with a unique cross-fiber construction to provide greater drywall joint strength than conventional fiberglass leno-weave mesh tapes. This self-adhesive tape goes on quickly, eliminating the bedding coat. Finished joints are accomplished in two coats by using setting-type joint compound. It is not recommended to use drying-type compounds with fiberglass tape.

AND FIBERGLASS JOINT TAPE	PRODUCT DATA
 Self-adhesive tape—no bedding coat needed Smooth joints in only two coats Use with setting-type joint compounds for one-day joint finishing Meets ASTM C475, Type II Meets ASTM D3273 for mold resistance 	AVAILABLE IN: 75' roll, 250' roll; 1-7/8" wide, 2-1/2" wide
MESH TAPE	PRODUCT DATA
 Pressure-sensitive adhesive backing permits quick, self-stick, hand application Creates a tough, durable and crack-resistant veneer plaster assembly Provides an excellent surface for keying plaster during embedding due to open weave 	AVAILABLE IN: 150' roll in 1-7/8" wide; 75' roll, 300' roll in 2" wide
TYPE P & TYPE S	PRODUCT DATA
 Type S for staple attachment is available in 2-1/2" wide Type P for pressure-sensitive attachment is available in two sizes: 2" and 2-1/2" wide Open weave of tape provides excellent keying of plaster during embedding 	AVAILABLE IN: 300' roll; 2" wide, 2-1/2" wide
	 Self-adhesive tape—no bedding coat needed Smooth joints in only two coats Use with setting-type joint compounds for one-day joint finishing Meets ASTM C475, Type II Meets ASTM D3273 for mold resistance MESH TAPE Pressure-sensitive adhesive backing permits quick, self-stick, hand application Creates a tough, durable and crack-resistant veneer plaster assembly Provides an excellent surface for keying plaster during embedding due to open weave TYPE P & TYPE S Type S for staple attachment is available in 2-1/2" wide Type P for pressure-sensitive attachment is available in two sizes: 2" and 2-1/2" wide Open weave of tape provides excellent keying of plaster during embedding embedding

Produces highly crack-resistant veneer plaster assemblies

BEAD AND TRIM

PAPER-FACE METAL CORNER

For the most cost-effective, problem-free, beautiful corners, choose USG Sheetrock® and Beadex® Brand Paper-Faced Metal Corner Bead and Trim. Fast, easy installation means reduced labor costs, while superior product performance eliminates costly job callbacks, saving money and ensuring customer satisfaction. With the tape-on versions, nailing is not required, so installation and corner alignment are easier, and there are no nails to pop when wood framing shrinks. Nail-on versions of the bead and trim are designed for applications where nailing or other mechanical fastening is desired. They use the same paper-faced metal technology to provide excellent bond adhesion qualities for joint compounds, textures and paints. The unique green "nose coating" on the paper tape covering resists scuffing and fuzzing from knives and sanding. The paper tape covering ensures excellent adhesion of joint compounds, textures and paints for a strong, smooth finish.

USG Sheetrock® and Beadex® Brand Paper-Faced Metal Corner Bead and Trim provide superior resistance to edge cracking and chipping for a look that stays beautiful despite the stresses of normal building movement and everyday wear and tear. In fact, USG warrants that its beads and trims will not edge crack for the lifetime of the structure using recommended application techniques.

All Sheetrock® Brand Bead and Trim products are available in the East Region. All Beadex® Brand Bead and Trim products are available in the West Region. Please refer back to page 5 for regional details.

90° AND OFFSET OUTSIDE CORNER BEAD

USG SHEETROCK® BRAND PAPER-FACED METAL CORNER BEAD OUTSIDE CORNER, TAPE-ON (B1W, B1XW, B1XXW, B1 SUPER WIDE)

ALSO AVAILABLE IN USG BEADEX* BRAND



STYLE

B1W					
B1W EL					
B1XW					
B1XW EL	•••	•••			
B1XW NB			 		
B1XW ELNB			 		
B1 Super Wide					
B1XXW EL*					

* Only available in Beadex brand.



USG SHEETROCK* BRAND PAPER-FACED METAL CORNER READ OUTSIDE CORNER TAPE-ON (MICRO BEAD)

ALSO AVAILABLE IN USG **BEADEX* BRAND**

STYLE Micro Beac



Use for 90° outside corners. Suitable for use on any thickness of wallboard. Standard lengths: 8', 9', 10'. Meets ASTM C1047.

DIMENSIONS

A	В	с	D
3/4"	13/16″	9/16″	3/4"
3/4"	11/16″	11/16″	3/4"
5/8″	15/16″	15/16″	5/8"
5/8″	13/16″	13/16″	5/8″
5/8″	15/16″	11/16″	5/8″
5/8″	13/16″	13/16″	5/8″
11/16″	1-1/16″	1-1/16″	11/16″
3/4"	1-1/4"	1-1/4"	3/4"

Note: XW = Extra Wide; XXW = Extra Extra Wide; EL = Even Leg; NB = No Bead.



Designed with a wider 1" by 1" profile that's easier to install on all cut edges. Reduced bead height results in less use of joint compound. In most cases, reduces the amount of compound needed by one coat. Standard lengths: 8', 10', 12'. Meets ASTM C1047.

DIMENSIONS

Α	В	с	D
3/4"	15/16″	15/16″	3/4"



* For regional map please refer to page 5

90° AND OFFSET OUTSIDE CORNER BEAD CONT.

USG SHEETROCK® BRAND PAPER-FACED METAL CORNER BEAD OFFSET OUTSIDE, CORNER, TAPE-ON (B1 OS)

Designed for 135° corners. Offset bead is designed to give a true offset corner with a smaller bead height requiring less compound to finish. Can be used on any thickness of wallboard. Standard lengths: 8', 9', 10'. Meets ASTM C1047.





DIMENSIONS D STYLE Α в с B1OS 5/8″ 3/4" 1/2" 5/8″ Note: OS = Offset

USG BEADEX[®] BRAND PAPER-FACED METAL CORNER BEAD OUTSIDE CORNER, NAIL-ON (ULTRA BEAD)



USG BEADEX[®] BRAND PAPER-FACED METAL CORNER BEAD

OUTSIDE CORNER, TAPE-ON (MEGA BEAD)

Use for applications where nailing or other mechanical fastening is required. Can be fastened to 1/2" or 5/8" drywall with nails, staples or screws. Standard lengths: 8', 9', 10'. Meets ASTM C1047.

DIMENSIONS





Use for 90° outside corners. Suitable for use on any thickness of wallboard. Standard lengths: 8', 10'. Meets ASTM C1047.

DIMENSIONS





USG SHEETROCK[®] BRAND PAPER-FACED METAL CORNER TRIM INSIDE CORNER, TAPE-

ON (B2)

90° AND OFFSET INSIDE CORNER

ALSO AVAILABLE IN USG BEADEX* BRAND STYLE B2



ALSO AVAILABLE IN USG BEADEX* BRAND

Standard lengths: 8', 9', 10'.







SOFTLINE BULLNOSE AND OFFSET OUTSIDE CORNER BEAD

USG SHEETROCK" BRAND PAPER-FACED METAL CORNER BEAD 3/4" BULLNOSE OUTSIDE CORNER, TAPE-ON (SLOC)	Designed for 135° offset corners. Standard length



STYLE SLOC 3/4" Radi







Designed to form a true inside (90°) corner. For use with any thickness of wallboard. Standard lengths: 8', 9', 10'. Meets ASTM C1047.

DIMENSIONS

A	В	с	D
5/8″	3/8"	3/8"	5/8″

Designed for a 135° offset angle on inside corners greater than 90°. For use on any thickness of wallboard.

DIMENSIONS

A	В	с	D
5/8″	5/8"	5/8″	5/8″

et angles. Speeds application and eliminates need on framing members for fastening gths: 8', 9', 10'. Meets ASTM C1047.

DIMENSIONS

A	RADIUS	В
5/8″	3/4"	5/8″



SOFTLINE BULLNOSE AND OFFSET OUTSIDE CORNER BEAD CONT.

USG SHEETROCK* BRAND PAPER-FACED METAL CORNER BEAD 1" BULLNOSE OFFSET OUTSIDE CORNER, TAPE-ON (SLOC OS)

Installs easily to form a smooth rounded outside corner. The 3/4" radius can be used for 1/2" or 5/8" drywall. Standard lengths: 8', 9', 10'. Meets ASTM C1047.

•••••••••••••••••••••••••••••••••••••••
ALSO AVAILABLE IN USG
BEADEX [®] BRAND



RADIUS STYLE Α в 3/4" 3/4" SLOC OS Note: OS = Offset



DIMENSIONS

USG BEADEX* BRAND PAPER-FACED METAL CORNER BEAD 1-1/2" BULLNOSE OUTSIDE CORNER, TAPE-ON (DANISH™)



USG SHEETROCK[®] BRAND PAPER-FACED METAL CORNER

BEAD 3/4" BULLNOSE OUTSIDE

CORNER, TAPE-ON (SANTA

ALSO AVAILABLE IN USG

BEADEX® BRAND

FE™)

Bead is similar to the SLOC series, except for a 1-1/2" radius. Can be used for 1/2" or 5/8" drywall. Standard lengths: 10'. Meets ASTM C1047.

DIMENSIONS





Provides economical alternative for bullnose corners. Suitable for use on any thickness of wallboard. Standard
lengths: 8′, 9′, 10′.





USG SHEETROCK* BRAND PAPER-FACED METAL CORNER BEAD 1/2" BULLNOSE OUTSIDE CORNER, TAPE-ON (BABY BULL®)

ALSO AVAILABLE IN USG BEADEX* BRAND



Provides a narrower finished look with a smaller radius compared to other bullnose profiles. Also excellent for trimming around windows. Can be applied over 1/2" or 5/8" drywall. Standard lengths: 8', 9', 10'. Meets ASTM C1047.

DIMENSIONS

STYLE	А	RADIUS	В
Baby Bull®	5/8″	1/2"	5/8"







STYLE

SLOC N

Note: OS = Offset



USG SHEETROCK[®] BRAND

PAPER-FACED METAL CORNER BEAD 3/4" BULLNOSE OUTSIDE

CORNER, NAIL-ON (SLOC N)

ALSO AVAILABLE IN USG

USG BEADEX* BRAND PAPER-

FACED METAL CORNER BEAD

3/4" BULLNOSE OUTSIDE

CORNER, NAIL-ON (SANTA

BEADEX* BRAND

STYLE SLOC NXW

Note: NXW = Nail-On Extra Wide



10'. Meets ASTM C1047.

USG BEADEX* BRAND PAPER-FACED METAL CORNER BEAD 3/4" BULLNOSE OFFSET OUTSIDE CORNER, TAPE-ON (BABY BULL[®] OS)

AVAILABLE IN WEST **REGION ONLY**



Baby Bull® OS Note: OS = Offset

STYLE







Use for smooth, rounded corners where nailing or other mechanical fastening is required. Can be fastened to 1/2" or 5/8" drywall with nails, staples or screws. Standard lengths: 8', 9', 10'. Meets ASTM C1047.

USG SHEETROCK BRAND ONLY AVAILABLE IN PREMASKED L (5/8")

DIMENSIONS

A	RADIUS	В
9/16″	3/4"	9/16″

Provides economical alternate for bullnose corners. Can be fastened with nails or screws. Standard lengths: 8', 9.' 10'. Meets ASTM C1047.

DIMENSIONS

A	RADIUS	
5/8″	3/4"	

Use for applications where nailing or other mechanical fastening is required. Creates 135° offset outside corner. Standard lengths: 8', 9', 10'. Meets ASTM C1047.

DIMENSIONS

A	RADIUS
7/8″	3/4"

Provides economical alternate for bullnose corners. Can be fastened to nails or screws. Standard lengths: 8', 9',

DIMENSIONS

Α	RADIUS	В
5/8″	3/4"	5/8″

SOFTLINE BULLNOSE AND OFFSET OUTSIDE CORNER BEAD CONT.

USG BEADEX® BRAND PAPER-FACED METAL CORNER BEAD 1" BULLNOSE OFFSET OUTSIDE CORNER, NAIL-ON (SLOC NOS)

USG BEADEX® BRAND PAPER-FACED METAL CORNER BEAD

1/2" BULLNOSE OUTSIDE CORNER, NAIL-ON (BABY

BULL® N)



Narrower bullnose "look" designed for 135° outside corner offsets. Standard lengths: 8', 10'. Meets ASTM C1047.

DIMENSIONS

STYLE	А	RADIUS	В
SLOC NOS	1-1/16″	1″	1-1/16″

Note: NOS = Nail-On Offset



Provides a narrower finished look with a smaller radius compared to other bullnose profiles. Also excellent for trimming around windows. Use where nailing or other mechanical fastening is required. Standard lengths: 8', 9,'10'. Meets ASTM C1047.

DIMENSIONS

STYLE	А	RADIUS	В
Baby Bull® N	3/4"	1/2"	3/4"
Note: N = Nail-On			



L-TRIMS

ALSO AVAILABLE IN USG BEADEX* BRAND

USG SHEETROCK[®] BRAND PAPER-FACED METAL TRIM "L" SHAPED, TAPE-ON (B4 SERIES)

(1/2") and B4 NB (1/2").

STYLE	А	В	с	
B4 (1/2")	1/2"	15/16″	1-5/16″	
B4 (5/8")	5/8″	13/16″	1-5/16″	
B4 (1")	1″	15/16″	1-3/8"	
B4 NB (1/2")	1/2"	15/16″	1-5/16″	
B4 NB (5/8")	5/8″	13/16″	1-5/16″	
Note: NB = No Bead				



USG BEADEX[®] BRAND PAPER-FACED METAL TRIM PREMASKED "L" SHAPED, TAPE-ON (PREMASKED L)







J-TRIMS

USG SHEETROCK [®] BRAND	
PAPER-FACED METAL TRIM "J"	
SHAPED, TAPE-ON (B9)	

ALSO AVAILABLE IN USG BEADEX® BRAND

*USG SHEETROCK BRAND

Standard lengths: 7', 8', 10'.









Use where wallboard abuts with suspended ceilings, beams, plaster, masonry and concrete walls, as well as untrimmed door and window jambs. Standard lengths: 8', 9', 10'. Meets ASTM C1047, with the exception of B4

DIMENSIONS



Provides a serrated paper strip that protects the adjacent surface of ceiling or wall intersection during finishing and decorating applications. Simply tear away the protective strip after the job is completed, leaving virtually no cleanup to the adjacent surface. No bead. Standard lengths: 8', 10'. Meets ASTM C1047.

DIMENSIONS

A	В	С	D
1/2″	7/8″	1-5/16″	1-11/16" tear off
5/8″	3/4"	1-5/16″	1-11/16" tear off

Tape-on "J"-shaped trim completely surrounds the rough edge of the wallboard, providing a strong and clean corner. Tape-on application eliminates frustration with nailing and nail shrink back. Can be used for finishing off bifold closet doors, as well as under all door and window encasements, and to finish rough drywall ends.

DIMENSIONS

A	В	С	D
1/2″	9/16″	5/8″	1-1/16″
1/2″	5/8″	9/16″	1-1/16″

USG SHEETROCK BRAND ONLY AVAILABLE IN B9 J (1/2")

REVEAL TRIMS

USG® BEADEX BRAND PAPER-FACED METAL TRIM REVEAL, TAPE-ON (REVEAL NB)

This modified tape-on "L"-shaped trim solves a variety of problems associated with reveal details on soffits, wall areas, ceilings, light boxes and other interior architectural components. Reveal NB features a paper flange on both trim legs. The additional paper flange eliminates the need to caulk the edge of reveal details, providing a cleaner and straighter line. Available only in No Bead. Standard lengths: 10'. Meets ASTM C1047.



USG BEADEX® BRAND

TAPE-ON REVEAL TRIM

SHADOWLINE,

DIMENSIONS STYLE Α в с D Reveal NB (1/2") 15/16" 1/2″ 1/2″ 3/4″ 5/8″ Reveal NB (5/8") 15/16" 5/8″ 5/8″ Note: NB = No Bead



Designed to provide a reveal or "Shadowline" where wallboard abuts with a suspended ceiling. Standard lengths: 10'. Meets ASTM C1047.

DIMENSIONS

STYLE	А	В	с	D
SL (1/2")	1/2″	1/2"	15/16″	1-1/4″
SL (5/8")	5/8″	5/8″	7/8"	15/16″





USG SHEETROCK* BRAND B1 FLEXIBLE METAL CORNER, TAPE-ON OUTSIDE FLEXIBLE CORNER (B1 BEADED FLEX)

ALSO AVAILABLE IN USG BEADEX* BRAND





METAL CORNER BEAD

Metal corner bead provides protection and neat finished edges for corners, gypsum panels at window and door jambs, ceiling angles and intersections where panels abut other materials.

USG SHEETROCK* BRAND DUR-A-BEAD* CORNER BEAD



*Limited availability on East Coast

TAPE-ON FLEXIBLE OUTSIDE AND INSIDE CORNER BEAD

USG SHEETROCK® BRAND FLEXIBLE METAL TAPE-ON CORNER BEAD, TAPE-ON FLEXIBLE CORNER (FLEX TAPE)

Can be formed to fit any inside or outside angle. Available in 2-1/16" width that has two 7/16"-wide galvanized rust-resistant steel strips with a 1/16" gap between the strips. Product is suitable for any thickness of wallboard. Available in 100' rolls.

ALSO AVAILABLE IN USG BEADEX* BRAND





Proprietary style designed specifically to make straight, strong outside corner angles. Available in 3" width and manufactured with two 3/4" galvanized steel strips laminated to paper tape with a flexible gap between the strips. B1 Beaded Flex has a unique raised bead (nose) in the flexible gap to provide faster, easier finishing with joint compound. For use on any wallboard thickness. Standard lengths: 8', 9', 10'. Meets ASTM C1047.

DIMENSIONS

Α	В	с	D
11/16″	3/4"	3/4"	11/16″



Durable metal bead that's manufactured with galvanized steel. Installs easily by crimping or nailing to steel or wood framing through panels. Protects external corners, angles and panel intersections in drywall construction, and is concealed with our joint compounds, delivering a smooth, finished corner that protects from impact. Standard lengths: 8', 9', 10', 12'. Meets ASTM C1047.

INTERIOR TEXTURES

POWDER TEXTURES

USG powder textures provide an economical interior wall and ceiling solution for a wide range of patterns. Conveniently packaged in bags, these textures allow you to transport more at once and require less storage space.

USG SHEETROCK[®] BRAND QT POLY CEILING SPRAY TEXTURE: FI



- Ideal for new construction and for rene
- · Hides minor surface defects with an att
- Choice of three high-style finishes
- Easy-pumping, low-cost spray applicat

USG SHEETROCK[®] BRAND SPRAY TEXTURE: UNAGGREGATED



- and spatter/knockdown
 - Superior open time for hand-tooled kno • Excellent surface relief (standout), low
 - Not washable unpainted—overpaint wl

USG SHEETROCK[®] BRAND TUF-TEX[®] WALL AND CEILING TEXTUR



- orange peel Conceals minor surface defects • Spray, brush or roller application
 - Dries to a hard white finish—overpaint

USG BEADEX[®] BRAND QUICK SPRAY DECORATIVE TEXTURE



- Designed for spray application over gy interior wall and ceiling surfaces where patterns are desired
- Dries to a firm, soft-tone white surface
- Provides lower shrinkage than texturing with joint compound

SURFACING SOLUTIONS

USG offers a wide variety of textures and finishes to hide minor surface blemishes and provide distinctive interior styling. These products are fast and easy to apply and quick drying, saving labor time to preserve job profits.

AND QT POLY CEILING SPRAY TEXTURE: FINE, MEDIUM AND COARSE	PRODUCT DATA
 For striking acoustical appearance on interior ceilings Ideal for new construction and for renewing old ceilings Hides minor surface defects with an attractive texture Choice of three high-style finishes Easy-pumping, low-cost spray application 	AVAILABLE IN: 32 lb. bag, 40 lb. bag
AND SPRAY TEXTURE: UNAGGREGATED	PRODUCT DATA
 For a variety of light, appealing textures in interiors, including spatter and spatter/knockdown Superior open time for hand-tooled knockdown finishes Excellent surface relief (standout), low shrinkage Not washable unpainted—overpaint when dry 	AVAILABLE IN: 50 lb. bag
AND TUF-TEX* WALL AND CEILING TEXTURE	PRODUCT DATA
 For diverse texture patterns from bold spatter/knockdown to light orange peel Conceals minor surface defects Spray, brush or roller application Dries to a hard white finish—overpaint when dry 	AVAILABLE IN: 50 lb. bag
QUICK SPRAY DECORATIVE TEXTURE	PRODUCT DATA
 Designed for spray application over gypsum panels and most other interior wall and ceiling surfaces where moderate to bold texture patterns are desired Dries to a firm, soft-tone white surface 	REGIONAL AVAILABILITY: Auburn AVAILABLE IN: Unaggregated;

50 lb. bag

READY-MIXED TEXTURES

Ideal for repair and remodel projects, USG ready-mixed textures eliminate the screening of lumps that occur in the mixing process, which means less wear and tear on equipment.

	AND SPRAY TEXTURE	PRODUCT DATA
USG PERSONAL Spray Texture Texture Rociada	 Spray texture with ready-mixed convenience For a variety of light, appealing textures in interiors, such as spatter, spatter/knockdown and orange peel Excellent surface relief (standout); low shrinkage Not washable unpainted—overpaint when dry 	REGIONAL AVAILABILITY: Fort Dodge / Dallas / Galena Park / Phoenix / Sigurd / Torrance / Auburn AVAILABLE IN: 3.5 gal. carton, 4.5 gal. cartor
SG SHEETROCK [®] BR	AND TEXOLITE* SANDED PASTE STIPPLE Provides a fine, light sand finish	PRODUCT DATA

- Latex formula dries to a durable, natural white finish Conceals minor surface defects Spray, brush or roller applied

USG SHEETROCK® BRAND SAND FINISH PAINT ADDITIVE



- For creating textured walls and ceilings
- Also ideal for creating a non-skid surface on decks, steps, etc.

Works in all paints and varnishes—oil-based or latex-based interior or exterior

- Amount used can be varied to provide a customized texture
- Remains suspended during application to ensure a uniform finish

USG BEADEX® BRAND FASTEX™ WALL AND CEILING SPRAY TEXTURE



- Vinyl formulation for texturing interior, above-grade surfaces
- Designed for spray application over gypsum panel, concrete, and most other interior wall and ceiling surfaces where moderate to bold texture patterns are desired
- Dries to a white surface, but should be overpainted when dry

PRODUCT DATA

Gypsum

AVAILABLE IN:

1 gal. pail, 5 gal. pail

REGIONAL AVAILABILITY: East Chicago / Fort Dodge / Gypsum

AVAILABLE IN: 8 oz. tub, 30 oz. box

PRODUCT DATA

Auburn

AVAILABLE IN:

3.5 gal. carton

REGIONAL AVAILABILITY:

PLASTER

VENEER PLASTER FINISHES AND BASECOATS

USG veneer plaster systems offer the opportunity to trim days from interior finishing schedules and provide strong, highly abrasion-resistant surfaces. These products are designed for one- or two-coat work over gypsum bases or directly to concrete block or properly prepared monolithic concrete. Both one- or two-coat applications offer a truly monolithic surface that is superior for critical light conditions.

Plaster products are GREENGUARD certified and qualify as low VOC emitting materials (CDPH Standard Method V1.1, also known as CA Section 01350).

VENEER FINISHES



- Usually ready for next-day decoration with a latex-based breather-type paint
 - When used with USG Imperial® Gypsum Base, provides fire resistance

USG APEX™ VENEER FINISH



- Versatile, fuller bodied veneer finish plaster that may be textured, floated or finished smooth
- One- and two-coat veneer plaster systems
- Easy mixing
- Extended set
- Fast applying—permits next-day decorating

USG NORFOLK[™] VENEER FINISH



- Provides white finish that may be left undecorated if found acceptable (painting recommended)
- Fast finishing, usually ready for next-day decoration with a latex-base breather-type paint (PVA paints not recommended)



NISH	- SAN	DED
1311	- 541	

PRODUCT DATA

AVAILABLE IN:

50 lb. bag

PRODUCT DATA

AVAILABLE IN: 50 lb. bag

PRODUCT DATA AVAILABLE IN: 50 lb. bag PRODUCT DATA • Versatile veneer plaster that may be finished smooth, float or textured AVAILABLE IN: 50 lb. bag

VENEER BASECOATS

USG DIAMOND[®] VENEER BASECOAT



- For economical two-coat residential and light-commercial applications • Superior workability for faster, easier application
- Excellent base for a variety of plaster finishes

• Durable and stable, especially in high-traffic areas

• High coverage—as much as 4,000 to 5,000 sq. ft. per ton

USG IMPERIAL[®] VENEER BASECOAT



- Permanent bond
- When used with USG Imperial[®] Gypsum Base, provides fire resistance
- Can be applied direct to concrete block or over a bonding agent to monolithic concrete

CONVENTIONAL PLASTER FINISHES AND BASECOATS

USG conventional plaster systems provide the highest-quality finish and the capability to create complex high-end surfaces such as vaults, domes and columns. These products feature excellent acoustical performance, proven fire resistance, increased abuse resistance and design flexibility, and are the best system to attain a uniform, monolithic, blemish-free, smooth surface with excellent wear resistance.

CONVENTIONAL FINISHES

USG RED TOP [®] GAUGI	ING PLASTER: QUICK SET, SLOW SET AND PERLITE AGGREGATE	PRODUCT DATA
Unity Carlos Carlos Parter Carlos Parter Carlos Parter Estation Carlos Parter Estation Carl	 Mixes smoothly and easily Provides smooth-trowel or sand-float lime-putty finishes for normal interior walls and ceilings Produces hard, crack and abrasion-resistant surfaces 	AVAILABLE IN: 50 lb. bag



- For filling and smoothing monolithic concrete ceilings and columns located above grade
- Easily applied—no extra bonding agent needed
- Dries to a fine white decorative surface

USG STRUCTO-GAUGE® GAUGING PLASTER: QUICK SET AND SLOW SET

• Also ideal for drywall tape embedding and first coat over bead

AVAILABLE IN:

50 lb. bag

PRODUCT DATA

AVAILABLE IN:

50 lb. bag

PRODUCT DATA

PRODUCT DATA

AVAILABLE IN:

50 lb. bag



- For blending with lime putty to create a durable, high-crack-resistant finish
- Retemperable; can be floated for an extended time period
- Permits mixing large batches and job finishing when sand-float finished

CONVENTIONAL BASECOATS

USG STRUCTO-LITE[®] BASECOAT PLASTER



- Mill-mixed perlite-aggregate gypsum plaster; requires only the addition of water at the job site
- Ideal where it is not desirable to mix aggregate with plaster on the job
- Lightweight plaster; weighs less than half as much as sanded plaster
- Excellent for areas requiring highly insulated plaster

USG STRUCTO-BASE[®] GYPSUM PLASTER



- Develops higher strengths than conventional plasters (up to 2,800 psi compressive strength)
- Ideal for high-abuse areas, such as handball courts, security walls, hospital corridors and schools
- Recommended over metal lath with scratch and brown coats mixed 2 cu. ft. sand to 100 lbs. plaster





• Factory-prepared for trouble-free mixi • Excellent smoothness and troweling ch Consistent lime/gauging ratio

PLASTER	PRODUCT DATA
 For finishing conventional and veneer plaster interior surfaces Factory-prepared for trouble-free mixing Excellent smoothness and troweling characteristics Consistent lime/gauging ratio 	AVAILABLE IN: 50 lb. bag
S CEMENT	PRODUCT DATA

T DATA

T DATA

AVAILABLE IN: 50 lb. bag

PRODUCT DATA

AVAILABLE IN: 50 lb. bag

• For extremely high-strength conventional plaster applications

PRODUCT DATA

AVAILABLE IN: 50 lb. bag

CONVENTIONAL BASECOASTS CONT.

USG RED TOP [®] GYPSUM PLASTER		PRODUCT DATA
USG Cyprim Plaster Enkicido de Yeso Plaster de Gypre	 Multipurpose conventional basecoat plaster applications The most popular conventional gypsum basecoat plaster in the building industry For hand or machine application, or both; for use with sand or lightweight aggregates For plaster wall and ceiling assemblies requiring high fire-resistant and sound-isolating performance 	AVAILABLE IN: 50 lb. bag
USG RED TOP* GYPSUM PLASTER: WOOD FIBER PRODUCT DATA		



- For plaster wall and ceiling assemblies requiring high fire-resistant and sound-isolating performance
- Ideal as a scratch coat for metal lath applications
- Contains fine particles of selected wood fiber, needs addition of water only
- Develops higher strength than standard gypsum plasters

PLASTER ACCESSORIES

When conditions exist that affect the adhesion or the normal setting time of conventional plasters, veneer plasters, lime finish plasters and setting-type joint compounds, USG offers special additives in a variety of high-performance formulations.

USG GYPSUM PLASTER RETARDER: STANDARD STRENGTH



• For slowing the setting time of conventional plasters, veneer plasters, lime finish plasters and setting-type joint compounds

- Easily disperse into mixing water for quick addition to plaster mix
- Available in a Standard Strength formulation

USG GYPSUM PLASTER ACCELERATOR: STANDARD STRENGTH



USG MI Plaster I Adhesiv Agent I

• For reducing the setting time of plasters and setting-type joint compounds

• Available in a Standard Strength formulation to meet accelerated setting requirements • Easy to use



USG PLASTER BONDER: PINK AND CLEAR

- Provides enhanced and fortified adhesion to a wide variety of sound substrates
- Compatible with a large assortment of gypsum- and cement-based plasters
- Easily applied by brush, roller or spray to a uniform continuous film
- Clear or tinted to allow easy visual inspection when required
- Film dries quickly for same-day use, or may be left unplastered for up to 10 days

AVAILABLE IN: 50 lb. bag

30 USG Interior Finishing Products • PLASTER

PRODUCT DATA

AVAILABLE IN: 2.5 lb. resealable pouch

PRODUCT DATA

AVAILABLE IN: 3 lb. resealable pouch

PRODUCT DATA

AVAILABLE IN: 1 gal. resealable container, 5 gal. pail

PRIMERS

Whether you're skim coating an entire surface or spray applying a primer, USG primers and primer-surfacers minimize decorating problems and help achieve a superior paint job over interior gypsum board, wood and concrete surfaces.

USG SHEETROCK[®] BRAND FIRST COAT[™] PRIMER



- Ideal primecoat for interior gypsum board and concrete surfaces • Equalizes surface absorption and texture variations of substrate to minimize decorating problems
- Apply with brush, roller or spray equipment
- Dries white in less than 30 minutes—top coat in an hour

USG SHEETROCK[®] BRAND TUFF-HIDE[™] PRIMER-SURFACER

- TUFF-HIDE
- Achieves a Level 5 finish faster • High build spray for a smoother, more beautiful finish
- Durable coating hides minor surface defects
- Excellent for critical light areas
- Ideal finish for ceilings
- Dries white, can be tinted to match final top coat

SEALANTS

Applying sealant has proven to be the most cost-effective way to seal assemblies and prevent sound transmission. USG offers a variety of high-performing, resilient acoustical and Firecode® sealants that are approved for use in all Underwriters Laboratories Inc. (UL) fire-rated assemblies without affecting fire ratings.

Sealant products are GREENGUARD GOLD certified and qualify as low VOC emitting materials (CDPH Standard Method V1.1, also known as CA Section 01350).

USG SHEETROCK[®] BRAND ACOUSTICAL SEALANT

- Excellent sound-blocking material (supports high STC ratings)
- Superior performance as a fire caulk in UL Classified joint and through-penetration firestop systems
- Ideal for use in smoke and/or sound assemblies
- Meets ASTM C834 specifications for latex sealants
- Grade -18°C (0°F) low temperature flexibility, strong bond
- Low VOC

PREPARATION SOLUTIONS

Proper preparation is essential for producing the best possible painted finish. Also important for a superior paint job is the equalization of both the porosity and surface texture to minimize decorating problems. USG preparation solutions ensure your interiors are perfectly smooth and free of pockmarks, fine ridges and scuffed paper from sanding, providing a solid foundation for a superior finish.

PRODUCT DATA

AVAILABLE IN: 1 gal. pail, 5 gal. pail

PRODUCT DATA

AVAILABLE IN: 5 gal. pail



PRODUCT DATA

AVAILABLE IN: 29 oz. cartridge, 5 gal. pail

SEALANTS CONT.

USG SHEETI	PRODUCT DATA		
	 Superior performance as a fire caulk in UL Classified joint systems and through-penetration systems 	AVAILABLE IN: 29 oz. cartridge	
	 Ideal for use in smoke and/or sound assemblies 		

- Sound-blocking acoustical sealant (supports high STC ratings)
- Highly elastic for permanent flexibility and seal
- Meets ASTM C834

USG SHEETROCK[®] BRAND FIRECODE[®] COMPOUND

PRODUCT DATA

AVAILABLE IN:

15 lb. bag



- For use in providing firestop systems for floor and wall penetrations and head-of-wall construction joints
- Nontoxic; flame spread 0, smoke developed 0 when tested per ASTM E84
- Mixes quickly with water
- Complies with ASTM E814, CAN 4-S115 and UL 2079; recognized by ICBO (ER-5050)



34 USG Interior Finishing Products • SEALANTS

INTERIOR PATCH & REPAIR SOLUTIONS

Finished interior walls are subject to abuse and damage from time to time. USG has developed a line of repair products to deal with a variety of holes, cracks, dents and abrasions.

REPAIR PRODUCTS

USG SHEETROCK [®] B	RAND PLASTER OF PARIS	PRODUCT DATA
Protect of Parks	 For patching interior drywall and plaster walls and ceilings Sets hard in 30–50 minutes Can be used for casting, modeling and sculpting forms 	AVAILABLE IN: 3 lb. resealable pouch, 25 lb. bag
USG SHEETROCK [®] B	RAND DRYWALL REPAIR CLIPS	PRODUCT DATA
	 For fast, easy drywall repair of large holes (over 2") and areas damaged by water When used with fire-rated drywall, meets building code requirements for repairing one-hour fire-rated drywall partitions Suitable for both 1/2" and 5/8" drywall 	AVAILABLE IN: 6 clips, 12 drywall screws
USG SHEETROCK [®] B	RAND DUST CONTROL PATCH AND REPAIR COMPOUND	PRODUCT DATA
And Control of Control	 Unique formula binds up fine residue during sanding to form heavier particles that tend to fall to the floor instead of clouding the air Requires only two coats over bead and fasteners Bonds like a taping product for a tough, tight bond under most job conditions 	AVAILABLE IN: 1 qt. tub

- Combines all-purpose, single-package convenience with optimum taping and topping performance
- Easy to work from mud pan and knife

• Provides low shrinkage and a superior bond

• Ideal for laminating drywall and patching plaster surfaces

USG SHEETROCK[®] BRAND EASY SAND[™] JOINT COMPOUND

Easy to sand



- For one-day patching and joint finishing and next-day decoration
- Weighs up to 25% less than conventional setting-type compounds

AVAILABLE IN:

PRODUCT DATA

5- and 90-minute working times; 3 lb. resealable pouch

USG COMMODITY CODES

READY-MIXED JOINT COMPOUNDS

CONVENTIONAL WEIGHT

Product
USG Sheetrock® Brand All Purpose Joint Compound
USG Sheetrock® Brand All Purpose Joint Compound
USG Sheetrock [®] Brand All Purpose Joint Compound
USG Sheetrock® Brand All Purpose Joint Compound
USG Sheetrock [®] Brand All Purpose Joint Compound
USG Sheetrock® Brand Total™ Joint Compound
USG Sheetrock® Brand Taping Joint Compound
USG Sheetrock® Brand Topping Joint Compound
USG Sheetrock® Brand Topping Joint Compound
USG Beadex® Brand All Purpose Joint Compound
USG Beadex [®] Brand All Purpose Joint Compound
USG Beadex® Brand Taping Joint Compound
USG Beadex [®] Brand Topping Joint Compound

MIDWEIGHT

Product USG Sheetrock® Brand Midweight™ Joint Compound USG Sheetrock® Brand Midweight™ Joint Compound USG Sheetrock® Brand Midweight™ Joint Compound USG Sheetrock[®] Brand Total[™] Lite Joint Compound

LIGHTWEIGHT

Product	
USG Sheetrock [®] Brand Plus 3 [®] Joint Compound	
USG Sheetrock® Brand Plus 3® Joint Compound	
USG Sheetrock® Brand Plus 3® Joint Compound	
USG Sheetrock [®] Brand Plus 3 [®] Joint Compound	
USG Sheetrock® Brand Plus 3® Joint Compound	
USG Sheetrock [®] Brand Elite Finish Joint Compound	
USG Sheetrock® Brand Elite Finish Joint Compound	
USG Sheetrock® Brand Elite Finish Joint Compound	
USG Sheetrock [®] Brand Dust Control Patch and Repair Compou	
USG Sheetrock [®] Brand Dust Control Joint Compound	
USG Sheetrock® Brand Dust Control Joint Compound	
USG Sheetrock® Brand Dust Control Joint Compound	
USG Sheetrock® Brand Taping Lite Joint Compound	
USG Sheetrock® Brand Taping Lite Joint Compound	
USG Sheetrock® Brand Taping Lite Joint Compound	
USG Sheetrock® Brand Topping Lite Joint Compound	
USG Beadex® Brand All Purpose Lite Joint Compound	
USG Beadex® Brand All Purpose Lite Joint Compound	
USG Beadex® Brand All Purpose Lite Joint Compound	
USG Beadex® Brand Gold™ Lite Joint Compound	
USG Beadex® Brand Taping Lite Joint Compound	
USG Beadex® Brand Topping Lite Joint Compound	
USG Soquete™ Joint Compound	

Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
1.75 pt. tub	380270	6	72 cartons
3.5 qt. pail	385140	4	45 cartons
4.5 gal. pail	380501	-	48
3.5 gal. carton	380122	-	48
4.5 gal. carton	381450	-	48
3.5 gal. carton	385240	-	48
3.5 gal. carton	385242	-	48
4.5 gal. pail	380051	-	48
3.5 gal. carton	385236	-	48
4.5 gal. pail	388558	-	48
3.5 gal. carton	385252	-	48
3.5 gal. carton	385256	-	48
 3.5 gal. carton	385254	-	48

Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
4.5 gal. pail	380417	-	48
3.5 gal. carton	380423	-	64
4.5 gal. carton	380427	-	48 or 64
3.5 gal. carton	380281	-	64

Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
 	-		
 3.5 qt. pail	384013	4	45 cartons
 4.5 gal. pail	381466	-	48 or 72 unit pallet
3.5 gal. carton	383640	-	64
4.5 gal. carton	380285	-	48 or 64
4.5 gal. carton (tinted)	383645	-	48 or 64
3.5 gal. carton	380278	-	64
4.5 gal. carton	380279	-	64
 4.5 gal. carton (tinted)	380273	-	64
 1 qt. tub	380138	4 or 6	48 or 65 cartons
 3.5 qt. pail	384014	4	45 cartons
 3.5 gal. pail	380059	-	48
 3.5 gal. carton	380609	-	64
 4.5 gal. pail	384448	-	48
 3.5 gal. carton	385244	-	64
 4.5 gal. carton	380128	-	64
 3.5 gal. carton	385248	-	64
 3.5 qt. pail	384015	4	45 cartons
 4.5 gal. pail	380604	-	48
 3.5 gal. carton	385258	-	64
 3.5 gal. carton	385284	-	64
 3.5 gal. carton	385264	-	64
 3.5 gal. carton	385262	-	64
 3.5 gal. carton	380066	-	64

ULTRALIGHTWEIGHT

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock® Brand UltraLightweight Joint Compound	4.5 gal. pail	381903	-	48
USG Sheetrock® Brand UltraLightweight Joint Compound	3.5 gal. carton	381901	-	64
USG Sheetrock® Brand UltraLightweight Joint Compound	4.5 gal. carton	381902	-	48 or 64

DRYING-TYPE JOINT COMPOUNDS

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock® Brand All Purpose Joint Compound	25 lb. bag	383700	-	60 or 120
USG Sheetrock® Brand A/P Lite® Joint Compound	20 lb. bag	380081	-	120

SETTING-TYPE JOINT COMPOUNDS

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock® Brand Easy Sand™ 5 Joint Compound	3 lb. resealable bag	384024	6	48 cartons
USG Sheetrock® Brand Easy Sand™ 90 Joint Compound	3 lb. resealable bag	384025	6	48 cartons
USG Sheetrock® Brand Easy Sand™ 5 Joint Compound	18 lb. bag	384150	-	60 or 120
USG Sheetrock® Brand Easy Sand™ 20 Joint Compound	18 lb. bag	384214	-	60 or 120
USG Sheetrock® Brand Easy Sand™ 45 Joint Compound	18 lb. bag	384210	-	60 or 120
USG Sheetrock® Brand Easy Sand™ 90 Joint Compound	18 lb. bag	384211	-	60 or 120
USG Sheetrock® Brand Easy Sand™ 210 Joint Compound	18 lb. bag	384212	-	60 or 120
USG Sheetrock [®] Brand Durabond [®] 20 Joint Compound	25 lb. bag	380581	-	60 or 120
USG Sheetrock® Brand Durabond® 45 Joint Compound	25 lb. bag	381110	-	60 or 120
USG Sheetrock® Brand Durabond® 90 Joint Compound	25 lb. bag	381630	-	60 or 120
USG Sheetrock® Brand Durabond® 210 Joint Compound	25 lb. bag	381710	-	120
USG Beadex® Brand Silver Set™ 5 Joint Compound	18 lb. bag	384153	-	48
USG Beadex® Brand Silver Set™ 20 Joint Compound	18 lb. bag	385266	-	48
JSG Beadex® Brand Silver Set™ 40 Joint Compound	18 lb. bag	385268	-	48
USG Beadex® Brand Silver Set™ 90 Joint Compound	18 lb. bag	385272	-	48

CONCRETE FINISHING COMPOUNDS

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock® Brand Cover Coat® Compound	4.5 gal. pail	380951	-	48
USG Sheetrock® Brand Cover Coat® Compound	4.5 gal. carton	380910	-	48

JOINT TAPES

PAPER JOINT TAPES

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock* Brand Paper Joint Tape	75' roll; 2-1/16" wide	380041	24	100 cartons
USG Sheetrock® Brand Paper Joint Tape	250' roll; 2-1/16" wide	382175	20	36 cartons
USG Sheetrock® Brand Paper Joint Tape	500' roll; 2-1/16" wide	382198	10	40 cartons
USG Sheetrock® Brand Heavy Joint Tape	250' roll; 2-1/16" wide	382178	20	54 cartons
USG Sheetrock® Brand Heavy Joint Tape	500' roll; 2-1/16" wide	382199	10	40 cartons
USG Beadex® Brand Drywall Joint Tape	75' roll; 2-1/16" wide	380054	24	100 cartons
USG Beadex® Brand Drywall Joint Tape	250' roll; 2-1/16" wide	380046	20	36 cartons
USG Beadex® Brand Drywall Joint Tape	500' roll; 2-1/16" wide	380057	10	40 cartons
USG Beadex® Brand Perforated Drywall Joint Tape	500' roll; 2-1/16" wide	380050	10	40 cartons

FIBERGLASS JOINT TAPES

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock® Brand Fiberglass Joint Tape	75' roll; 1-7/8" wide	385170	24	60
USG Sheetrock® Brand Fiberglass Joint Tape	250' roll; 1-7/8" wide	385200	20	36
USG Sheetrock® Brand Fiberglass Joint Tape	250' roll; 2-1/2" wide	385201	20	36
USG Beadex® Brand Mesh Tape	75' roll; 2" wide	385173	30	36
USG Beadex® Brand Mesh Tape	300' roll; 2" wide	385191	28	28
USG Imperial® Tape: Type S	300' roll; 2-1/2" wide	364800	12	54
USG Imperial® Tape: Type P	300' roll; 2" wide	364850	12	54
USG Imperial® Tape: Type P	300' roll; 2-1/2" wide	364820	12	54

BEAD AND TRIM

90° AND OFFSET OUTSIDE CORNER BEAD

Product

USG Sheetrock® Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (B1W) USG Sheetrock® Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (B1XW EL) USG Sheetrock® Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (B1XW ELN USG Sheetrock[®] Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (B1 Super W USG Sheetrock® Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (Micro Bead USG Sheetrock® Brand Paper-Faced Metal Corner Bead Offset Outside Corner, Tape-On (B1 O USG Beadex® Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (B1W) USG Beadex® Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (B1W EL) USG Beadex® Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (B1XW) USG Beadex® Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (B1XW EL) USG Beadex® Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (B1XXW EL) USG Beadex® Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (B1XW ELNB) USG Beadex® Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (B1 Super Wide USG Beadex® Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (Micro Bead) USG Beadex[®] Brand Paper-Faced Metal Corner Bead Outside Corner, Tape-On (Mega Bead) USG Beadex® Brand Paper-Faced Metal Corner Bead Offset Outside Corner, Tape-On (B1OS) USG Beadex® Brand Paper-Faced Metal Corner Bead Outside Corner, Nail-On (Ultra Bead)

90° AND OFFSET INSIDE CORNER

Product

USG Sheetrock® Brand Paper-Faced Metal Corner Trim Inside Corner, Tape-On (B2) USG Sheetrock® Brand Paper-Faced Metal Corner Trim Offset Inside Corner, Tape-On (B2 OS) USG Beadex® Brand Paper-Faced Metal Corner Trim Inside Corner, Tape-On (B2) USG Beadex® Brand Paper-Faced Metal Corner Trim Offset Inside Corner, Tape-On (B2 OS)

SOFTLINE BULLNOSE AND OFFSET OUTSIDE CORNER BEAD

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock® Brand Paper-Faced Metal Corner Bead 3/4" Bullnose Outside Corner, Tape-On (SLOC)	8′, 9′, 10′	280320	50	60
USG Sheetrock* Brand Paper-Faced Metal Corner Bead 1" Bullnose Offset Outside Corner, Tape-On (SLOC OS)	8', 9', 10'	280310	50	60
USG Sheetrock® Brand Paper-Faced Metal Corner Bead 3/4″ Bullnose Outside Corner, Tape-On (Santa Fe™)	8', 9', 10'	280450	50	60
USG Sheetrock [®] Brand Paper-Faced Metal Corner Bead 1/2 [®] Bullnose Outside Corner, Tape-On (Baby Bull [®])	8', 9', 10'	280260	50	60
USG Sheetrock* Brand Paper-Faced Metal Corner Bead 3/4" Bullnose Outside Corner, Nail-On (SLOC N)	8', 9', 10'	281740	50	60
USG Beadex* Brand Paper-Faced Metal Corner Bead 3/4" Bullnose Outside Corner, Tape-On (SLOC)	7', 8', 9', 10', 12'	285700	50	60
USG Beadex" Brand Paper-Faced Metal Corner Bead 1" Bullnose Offset Outside Corner, Tape-On (SLOC OS)	8', 9', 10'	285690	50	60
USG Beadex" Brand Paper-Faced Metal Corner Bead 1-1/2" Bullnose Outside Corner, Tape-On (Danish''')	10'	285680	25	54

	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
	8', 9', 10', 12'	280380	50	60
	7', 8', 9', 10', 12'	280350	50	
NB)	8', 9', 10'	280330	50	60
Wide)	8', 10', 12'	280460	50	60
ad)	8', 9', 10'	280270	50	60
OS)	6', 7', 8', 9', 10', 12'	280280	50	60
	8', 9', 10', 12'	285740	50	60
	7', 8', 9', 10', 12'	680051	50	60
	8', 9', 10'	285730	50	60
	8', 9', 10', 12'	285720	50	60
	8', 9', 10', 12'	285610	50	60
)	8', 9', 10'	285850	50	60
de)	7', 8', 9', 10', 12'	285780	50	54
)	8', 9', 10', 12'	285670	50	60
	8', 10'	285620	50	60
5)	8', 9', 10'	285650	50	60
	8′, 9′, 10′	288300	50	60

	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
	8', 9', 10'	281530	50	60
S)	8′, 9′, 10′	281520	50	60
	8′, 9′, 10′	287910	50	60
	8′, 9′, 10′	287920	50	60

USG Beadex [®] Brand Paper-Faced Metal Corner Bead 1/2" Bullnose Outside Corner, Tape-On (Baby Bull*)	7', 8', 9', 10'	285640	50	60
USG Beadex [®] Brand Paper-Faced Metal Corner Bead 1/2" Bullnose Offset Outside Corner, Nail-On (Baby Bull [®] N)	8', 9', 10'	288970	50	60
USG Beadex [®] Brand Paper-Faced Metal Corner Bead 3/4" Bullnose Offset Outside Corner, Tape-On (Baby Bull® OS)	8′, 10′	288980	50	60
USG Beadex [®] Brand Paper-Faced Metal Corner Bead 3/4" Bullnose Outside Corner, Tape-On (Santa Fe™)	7, 8′, 9′, 10′	285760	50	60
USG Beadex [®] Brand Paper-Faced Metal Corner Bead 3/4" Bullnose Outside Corner, Nail-On (SLOC N)	8', 9', 10', 12'	288270	50	60
USG Beadex* Brand Paper-Faced Metal Corner Bead 1/2" Bullnose Offset Outside Corner, Tape-On (SLOC NOS)	8', 9', 10'	288280	50	60
USG Beadex [®] Brand Paper-Faced Metal Corner Bead 3/4" Bullnose Outside Corner, Nail-On (SLOC NXW)	8', 9', 10', 12'	288290	50	54
USG Beadex [®] Brand Paper-Faced Metal Corner Bead 3/4″ Bullnose Outside Corner, Nail-On (Santa Fe™ N)	8', 9', 10'	288260	50	60

L-TRIMS

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock* Brand Paper-Faced Metal Trim "L" Shaped, Tape-On (B4 1/2")	8', 9', 10'	281490	50	60
USG Sheetrock* Brand Paper-Faced Metal Trim "L" Shaped, Tape-On (B4 5/8")	8', 9', 10'	281480	50	60
USG Sheetrock* Brand Paper-Faced Metal Trim "L" Shaped, Tape-On (B4 NB 1/2")	8', 9', 10'	281440	50	60
USG Sheetrock® Brand Paper-Faced Metal Trim "L" Shaped, Tape-On (B4 NB 5/8")	8', 9', 10'	281450	50	60
USG Beadex® Brand Paper-Faced Metal Trim "L" Shaped, Tape-On (B41/2")	7', 8', 9', 10', 12'	287940	50	60
USG Beadex® Brand Paper-Faced Metal Trim "L" Shaped, Tape-On (B4 5/8")	7', 8', 9', 10'	287960	50	60
USG Beadex Brand Paper-Faced Metal Trim "L" Shaped, Tape-On (B4 1")	8', 10'	287990	50	60
USG Beadex® Brand Paper-Faced Metal Trim "L" Shaped, Tape-On (B4 NB 1/2")	8', 9', 10', 12'	287930	50	60
USG Beadex® Brand Paper-Faced Metal Trim "L" Shaped, Tape-On (B4 NB 5/8")	8', 9', 10', 12'	287970	50	60
USG Beadex® Brand Paper-Faced Metal Trim Premasked "L" Shaped, Tape-On (Premasked L 1/2")	8', 10'	288160	50	60
USG Beadex* Paper-Faced Metal Trim Premasked "L" Shaped, Tape-On (Premasked L 5/8")	8', 10'	288180	50	60

J-TRIMS

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock® Brand Paper-Faced Metal Trim "J" Shaped, Tape-On (B9J 1/2")	7', 8', 10'	281560	50	60
USG Beadex® Brand Paper-Faced Metal Trim "J" Shaped, Tape-On (B9J 1/2")	7', 8', 9', 10'	288000	25	54
USG Beadex* Brand Paper-Faced Metal Trim "J" Shaped, Tape-On (B9J 5/8")	7', 8', 10'	288010	25	54

REVEAL TRIMS

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Beadex® Brand Paper-Faced Metal Trim Reveal, Tape-On (Reveal NB 1/2")	10'	288020	50	60
USG Beadex® Brand Paper-Faced Metal Trim Reveal, Tape-On (Reveal NB 5/8")	10'	288030	50	60
USG Beadex® Brand Shadowline, Tape-On Reveal (SL 1/2")	10'	288040	50	60
USG Beadex* Brand Shadowline, Tape-On Reveal (SL 5/8")	10′	288050	50	60

TAPE-ON FLEXIBLE OUTSIDE AND INSIDE CORNER BEAD

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock* Brand Flexible Metal Tape-On Corner Bead, Tape-On Flexible Corner (Flex Tape 2-1/16")	25' roll, 100' roll	388810	10	40
USG Sheetrock* Brand B1 Flexible Metal Corner, Tape-On Outside Flexible Corner (B1 Beaded Flex)	8′, 9′, 10′	280430	50	60
USG Beadex* Brand Flexible Metal Tape-On Corner Bead, Tape-On Flexible Corner (Flex Tape 2-1/16")	25' roll, 100' roll	285870	10	24
USG Beadex [®] Brand B1 Flexible Metal Corner, Tape-On Outside Flexible Corner (B1 Beaded Flex)	8′, 9′, 10′	285750	50	56

METAL CORNER BEAD

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock [®] Brand Dur-A-Bead [®] Corner Bead (No. 103)	8′, 9′, 10′, 12′	283990	Varies by length	42

INTERIOR TEXTURES

POWDER TEXTURES

Product

USG Sheetrock® Brand QT Poly Ceiling Spray Texture: Fine USG Sheetrock® Brand QT Poly Ceiling Spray Texture: Medium USG Sheetrock® Brand QT Poly Ceiling Spray Texture: Medium USG Sheetrock® Brand QT Poly Ceiling Spray Texture: Coarse USG Sheetrock® Brand QT Poly Ceiling Spray Texture: Coarse USG Sheetrock® Brand Spray Texture: Unaggregated (Red) USG Sheetrock® Brand Spray Texture: Unaggregated (Gray)

USG Sheetrock® Brand Spray Texture: Unaggregated (Blue) USG Sheetrock Brand Spray Texture Unaggregated (Brown) USG Sheetrock[®] Brand Tuf-Tex[®] Wall and Ceiling Texture USG Beadex® Brand Quick Spray Decorative Texture

READY-MIXED TEXTURES

Product

USG Sheetrock® Brand Spray Textu	ire
USG Sheetrock® Brand Spray Textu	ıre
USG Sheetrock® Brand TexoLite® S	anded Paste Stipple
USG Sheetrock® Brand TexoLite® S	anded Paste Stipple
USG Sheetrock® Brand Sand Finish	Paint Additive
USG Sheetrock® Brand Sand Finish	Paint Additive
USG Beadex® Brand FasTex™ Wall a	and Ceiling Spray Texture

PLASTER

VENEER FINISHES

Product

USG Diamond® Veneer Finish
USG Diamond® Veneer Finish - Sanded
USG Imperial® Veneer Finish
USG Apex™ Veneer Finish
USG Norfolk™ Veneer Finish

VENEER BASECOATS

Product USG Diamond® Veneer Basecoat USG Imperial® Veneer Basecoat

CONVENTIONAL FINISHES

USG Red Top® Gaug	ing Plaster: Quick	Set	 	
USG Red Top® Gaug	ing Plaster: Slow S	Set		
USG Red Top® Gaug	ing Plaster: Perlite	e Aggregate		
USG Structo-Gauge	[®] Gauging Plaster	: Quick Set		
USG Structo-Gauge	[®] Gauging Plaster	: Slow Set		
USG Red Top® Finisl	n Plaster			
USG Red Top® Keen	es Cement			

CONVENTIONAL BASECOATS

Product

USG Structo-Lite® Basecoat Plaster
USG Structo-Base® Gypsum Plaster
USG Red Top® Gypsum Plaster
USG Red Top® Gypsum Plaster: Wood Fiber

Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
40 lb. bag	540500	-	60
32 lb. bag	542860	-	28 or 48
40 lb. bag	540795	-	32 or 60
32 lb. bag	542095	-	28 or 48
40 lb. bag	540790	-	32 or 60
50 lb. bag	545341	-	50
 50 lb. bag	545347	-	32 or 60
 50 lb. bag	544343	-	50
 50 lb. bag	545330	-	32 or 50
 50 lb. bag	540901	-	32 or 60
 50 lb. bag	385274	-	32 or 50

Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
3.5 gal. carton	540750	-	48
4.5 gal. carton	540752	-	48
1 gal. pail	545600	4	45 cartons
5 gal. pail	545601	-	32 or 48
8 oz. tub	380301	12	72 cartons
30 oz. box	380300	6	36 cartons
 3.5 gal. carton	385276	-	48

Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
50 lb. bag	162640	-	63
50 lb. bag	161980	-	63
50 lb. bag	164949	-	63
50 lb. bag	162101	-	63
 50 lb. bag	165650	-	63

Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
50 lb. bag	162681	-	63
50 lb. bag	164849	-	63

Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
50 lb. bag	163351	-	63
50 lb. bag	163352	-	63
50 lb. bag	163842	-	56
50 lb. bag	162581	-	63
50 lb. bag	162582	-	63
50 lb. bag	162850	-	63
50 lb. bag	165450	-	63

Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
50 lb. bag	163841	-	40
50 lb. bag	161410	-	63
50 lb. bag	163840	-	63
 50 lb. bag	167780	-	63

PLASTER ACCESSORIES

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Gypsum Plaster Retarder: Standard Strength	2.5 lb. resealable pouch	160217	6	48 cartons
USG Gypsum Plaster Accelerator: Standard Strength	3 lb. resealable pouch	160216	6	48 cartons
USG Plaster Bonder: Clear	1 gal. resealable container	160206	6	36 cartons
USG Plaster Bonder: Clear	5 gal. pail	160207	-	42
USG Plaster Bonder: Pink	1 gal. resealable container	161200	6	36 cartons
USG Plaster Bonder: Pink	5 gal. pail	161201	-	42

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock [®] Brand First Coat [™] Primer	1 gal. pail	544825	4	45 cartons
USG Sheetrock® Brand First Coat™ Primer	5 gal. pail	544822	-	48
USG Sheetrock® Brand Tuff-Hide™ Primer-Surfacer	5 gal. pail	542728	-	48

SEALANTS

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock® Brand Acoustical Sealant	29 oz. cartridge	030250	12	60 cartons
USG Sheetrock® Brand Acoustical Sealant	5 gal. pail	030260	-	48
USG Sheetrock® Brand Firecode® Compound	15 lb. bag	380020	-	120
USG Sheetrock® Brand Firecode® Smoke-Sound Sealant	29 oz. cartridge	030265	12	60 cartons

REPAIR PRODUCTS

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Sheetrock® Brand Plaster of Paris	3 lb. resealable pouch	380364	6	48 cartons
USG Sheetrock® Brand Plaster of Paris	25 lb. bag	380261	-	60 or 120 cartons
USG Sheetrock [®] Brand Drywall Repair Clips	6 clips, 12 drywall screws	380161	8 zip strips/carton (6 pieces/zip strip)	-
USG Sheetrock® Brand Dust Control Patch and Repair Compound	1qt. tub	380138	4 or 6	48 or 65 cartons
USG Sheetrock® Brand Easy Sand™ 5 Joint Compound	3 lb. resealable pouch	384024	6	48 cartons
USG Sheetrock® Brand Easy Sand™ 90 Joint Compound	3 lb. resealable pouch	384025	6	48 cartons



J1424/rev. 10-20

© 2020 USG Corporation and/or its affiliates. All rights reserved.

The trademarks USG, A/P LITE, APEX, BABY BULL, BEADEX, COVER COAT, DANISH, DIAMOND, DUR-A-BEAD, DURABOND, EASY SAND, FASTEX, FIRECODE, FIRST COAT, GOLD, IMPERIAL, MAC, MIDWEIGHT, NORFOLK, PLUS 3, RED TOP, SANTA FE, SELECT, SHEETROCK, SILVER SET, SOQUETE, STRUCTO-BASE, STRUCTO-GAUGE, STRUCTO-LITE, TEXOLITE, TOTAL, TUF-TEX, TUFF-HIDE, VLS, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

The trademark BAZOOKA is a trademark of Axia Acquisition Corporation.

NOTE

Products described here may not be available in all geographic markets. Consult your USG sales office representative for information.

The information in this document is subject to change without notice. USG Corporation assumes no responsibility for any errors that may inadvertently appear in this document.

NOTICE

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety and industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read Safety Data Sheets and related literature on products before specification and/or installation.

CONTACT INFORMATION

Manufactured by United States Gypsum Company 550 West Adams Street Chicago, IL 60661

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

CUSTOMER SERVICE

800 950-3839

TECHNICAL SERVICE

800 USG.4YOU (874-4968)

WEBSITES

usg.com usgdesignstudio.com

