

# VERSICO'S VERSIWELD® OUTSIDE CORNERS



## Installation

1. Place the center point of the VersiWeld Outside Corner over the outside intersection of the corner.
2. Begin welding at the innermost center point and work away from the center by first welding the vertical portion of the flashing.
3. Use a lower temperature setting on the heat welder than when welding reinforced TPO membrane. (Typically a setting of 6 on a scale of 10 is appropriate for welding VersiWeld TPO Outside Corners.)
4. Use the edge of the roller to crease the corner flashing into any membrane step-off to create a proper seal.
5. Probe all welded edges of the corner only once the material has completely cooled to ensure watertight performance.

## Precautions

1. Store VersiWeld TPO Outside Corners in a cool, shaded area and cover with light-colored, breathable, waterproof tarpaulins. VersiWeld TPO Outside Corners or TPO membrane that has been exposed to the weather prior to use must be prepared with Weathered Membrane Cleaner before hot-air welding.

## Overview

Let Versico simplify your next VersiWeld TPO installation with their prefabricated Outside Corners. VersiWeld TPO Outside Corners are pre-molded and are used for flashing outside corners on a variety of details. Installation is fast and easy with no cutting or stretching required.

Versico's VersiWeld TPO Outside Corners are part of the Certified Fabricated Accessory (CFA) Program. Certified Fabricated Accessories are the only factory-fabricated accessories that meet the stringent quality tolerances required to be included in a Versico warranted roofing system.

## Intended Uses

VersiWeld TPO Outside Corners are used for flashing outside corners on a variety of details.

## Features and Benefits

- Provide a substantial labor savings compared to field fabricating from non-reinforced flashing
- Pre-stretched, multi-wave design allows wrapping outside corners that are out of square and not exactly 90 degrees
- More consistent appearance than outside corners field-fabricated from flashing

### VERSIWELD OUTSIDE CORNERS TYPICAL PROPERTIES AND CHARACTERISTICS

Color	White, Gray, Tan
Thickness	0.060" (1.5 mm)
Packaging	12 per bag
Material	Injection-molded TPO



A SINGLE SOURCE FOR SINGLE-PLY ROOFING

**Versico, LLC** PO Box 1289, Carlisle, PA 17013  
Tel: **800.992.7663** Fax: 717.960.4036 Web: **www.versico.com**