

# V E R S I C O A D H E S I V E S

ADHESIVE	VOC COMPLIANT	MIXING REQUIRED	NOTES	COVERAGE RATE - FT <sup>2</sup> /GALLON (M <sup>2</sup> /GALLON)	MINIMUM APPLICATION TEMPERATURE - F° (C°)
<b>EPDM Membrane Adhesives and Primers</b>					
G200SA Substrate Adhesive	No	Yes	Can be used with all EPDM membranes.	60 (5.6)	N/A
x-23 Low-VOC Bonding Adhesive	Yes	Yes		60 (5.6)	N/A
Aqua Base 120 Bonding Adhesive <sup>1,3</sup>	Yes	Yes		100 – 120 (9 – 11)	40° (4°)
Low-VOC Bonding Adhesive 1168 <sup>1</sup>	Yes	Yes		60 (5.6)	40° (4°)
Solvent Free EPDM Bonding Adhesive <sup>1</sup>	Yes	No		100 (9)	40° (4°)
CAV-GRIP® 3V Adhesive/Primer <sup>1,**</sup>	Yes	No		1,000 (93)	25° (-4°)
V-150 Primer <sup>2</sup>	No	Yes		450 (41) <sup>2</sup>	N/A
Low-VOC Primer <sup>2</sup>	Yes	No		700 (65) <sup>2</sup>	N/A
<b>TPO Membrane Adhesives and Primers</b>					
TPO Bonding Adhesive	No	Yes	Can be used with all TPO membranes.	60 (5.6)	N/A
Low-VOC Bonding Adhesive	Yes	Yes		60 (5.6)	N/A
Aqua Base 120 Bonding Adhesive <sup>1,3</sup>	Yes	Yes		100 – 120 (9 – 11)	40° (4°)
Low-VOC Bonding Adhesive 1168 <sup>1</sup>	Yes	Yes		60 (5.6)	N/A
CAV-GRIP 3V Adhesive/Primer <sup>1,**</sup>	Yes	No		1000 (93)	25° (-4)
TPO Primer	No	Yes		250 (24)	N/A
Low-VOC Primer <sup>2</sup>	Yes	No		700 (65) <sup>2</sup>	N/A
<b>PVC Membrane Adhesives</b>					
Low-VOC PVC Bonding Adhesive <sup>1</sup>	Yes	Yes	Can be used with all PVC & KEE HP membranes.	60 (5.6)	N/A
Low-VOC HydroBond™ Water-Based Adhesive <sup>1,3</sup>	Yes	No	Can be used with all PVC membranes, not KEE HP membranes.	100 – 133 (9 – 12)	40° (4°)
CAV-GRIP PVC Adhesive <sup>1</sup>	Yes	No	Can only be used with PVC membranes, not KEE HP membranes.	750 (70)	35° (2°)
<b>VersiFleece® Membrane Adhesives</b>					
Flexible DASH <sup>1</sup>	Yes	No	Can be used with all VersiFleece TPO and VersiFleece PVC membranes.	(See Next Page)	25° (-4) <sup>4</sup>
Aqua Base 120 Bonding Adhesive <sup>1,3</sup>	Yes	Yes		100 – 120 (9 – 11)	40° (4°)
CAV-GRIP 3V Adhesive/Primer <sup>1,4,*</sup>	Yes	No	Vertical Wall Adhesive. Primer for unweathered Asphalt.	Single Sided Primer; 2,000 – 2,500 (111.5 – 232.3)* Double-Sided Wall Attachment 750 (69.7)	25° (-4)
Low-VOC HydroBond Water-Based Adhesive <sup>1,3</sup>	Yes	No	Can be used with VersiFleece KEE HP and VersiFleece PVC membranes.	100 – 133 (9 – 12)	40° (4°)
Cold Applied Bonding Adhesive <sup>1</sup>	Yes	No	Only for AC and VersiFleece KEE HP membranes.	67 (6)	40° (4°)
<b>Insulation Adhesives</b>					
Flexible DASH <sup>1</sup>	Yes	No	Can also be used for VersiFleece TPO and VersiFleece PVC membrane attachment.	Varies - Refer to Page 2	25° (-4)

<sup>1</sup> - Meets the requirements of SCAQMD.

<sup>2</sup> - For Clean membranes. Dusted membranes will have a lower coverage rate.

<sup>3</sup> - Adhesive must be protected from freezing

<sup>4</sup> - Only approved for wall applications

\* - Approximate Coverage

\*\* - Coverage rate for CAV-GRIP 3V is per 40 lb cylinder



## FLEXIBLE DASH ADHESIVES

### Approximate Coverage Rate

(Application rates may vary depending on ambient temperatures, surface, and substrate absorption rate)

<b>50 Gallon Drums</b>	<b>Full Spray</b>	<b>Splatter</b>	<b>4" o.c.</b>	<b>6" o.c.</b>	<b>12" o.c.</b>
FT <sup>2</sup>	5,000 – 10,000	18,000-20,000	6,700 – 9,000	10,000 – 12,500	20,000 – 25,000
M <sup>2</sup>	465 – 929	1,672-1,858	622 – 836	929 – 1161	1858 – 2323
<b>15 Gallon Drums</b>	<b>Full Spray</b>	<b>Splatter</b>	<b>4" o.c.</b>	<b>6" o.c.</b>	<b>12" o.c.</b>
FT <sup>2</sup>	1,800 – 3,000	5,400-6,000	2,110 – 2,700	3,000 – 3,750	6,000 – 7,500
M <sup>2</sup>	167 – 279	502-557	196 – 251	279 – 348	557 – 697
<b>5-Gallon Jugs</b>	<b>Full Spray</b>	<b>Splatter</b>	<b>4" o.c.</b>	<b>6" o.c.</b>	<b>12" o.c.</b>
FT <sup>2</sup>	600 – 1,000	1,800-2,000	670 – 900	1,000 – 1,250	2,000 – 2,500
M <sup>2</sup>	56 – 93	167-186	62 – 84	93 – 116	186 – 232
<b>Dual Tanks</b>	<b>Full Spray</b>	<b>Splatter</b>	<b>4" o.c.</b>	<b>6" o.c.</b>	<b>12" o.c.</b>
FT <sup>2</sup>	N/A	2,000-2,200	1,000 – 1,200	1,500 – 1,700	3,000 – 3,200
M <sup>2</sup>	N/A	186-204	93 – 111	139 – 158	279 – 297
<b>Dual Cartridge</b>	<b>Full Spray</b>	<b>Splatter</b>	<b>4" o.c.</b>	<b>6" o.c.</b>	<b>12" o.c.</b>
FT <sup>2</sup>	N/A	N/A	100 – 200	200 – 300	400 – 600
M <sup>2</sup>	N/A	N/A	9 – 18	18 – 28	37 – 55



A SINGLE SOURCE FOR SINGLE-PLY ROOFING

800.992.7663 • [www.versico.com](http://www.versico.com)