

The Williams Bros Corporation of America  
1330 Progress Drive  
Front Royal, Virginia 22630  
Toll Free (800) 255-5515  
Toll Free Fax (800) 822-5001  
Phone (540) 636-4444  
Fax (540) 636-4455  
Web Site www.wbdoors.com

## Product Guide Specification

Specifier Notes: This product guide specification is written according to the Construction Specifications Institute (CSI) Format, including *MasterFormat*, *SectionFormat*, and *PageFormat*, contained in the *CSI Manual of Practice*.

The section must be carefully reviewed and edited by the Architect to meet the requirements of the project and local building code. Coordinate this section with other specification sections and the drawings.

Delete all "Specifier Notes" when editing this section.

### SECTION 08 31 13

#### ACCESS DOORS

Specifier Notes: This section covers The Williams Brothers Corporation access doors. Consult Williams Brothers for assistance in editing this section for the specific application.

#### PART 1 GENERAL

##### 1.1 SECTION INCLUDES

- A. Access doors.

##### 1.2 RELATED SECTIONS

Specifier Notes: Edit the following list of related sections as required for the project. List other sections with work directly related to the access doors.

- A. Section 04 22 23 - Concrete Masonry Units.
- B. Section 06 10 53 - Miscellaneous Rough Carpentry.
- C. Section 09 23 00 - Gypsum Plastering.
- D. Section 09 21 16 - Gypsum Board Assemblies.

- E. Section 09 51 00 - Acoustical Ceilings.
- F. Section 23 33 00 – Air Duct Accessories.

### 1.3 SUBMITTALS

- A. Comply with Section 01 33 00 - Submittal Procedures.
- B. Product Data: Submit manufacturer's product data, including installation instructions.

Specifier Notes: Delete this paragraph if not required.

- C. Test Reports: Submit test reports or approvals from UL, Warnock Hersey, and California State Fire Marshall for fire-rated access doors.

### 1.4 DELIVERY, STORAGE, AND HANDLING

- A. Delivery: Deliver materials to site in manufacturer's original, unopened containers and packaging, with labels clearly identifying product name and manufacturer.
- B. Storage: Store materials indoors in a clean, dry area in accordance with manufacturer's instructions.
- C. Handling: Protect materials and finishes from damage during handling and installation.

## PART 2 PRODUCTS

### 2.1 MANUFACTURER

- A. The Williams Brothers Corporation, 777 Tapscott Road, Scarborough, Ontario, Canada M1X 1A2. Exclusively distributed by The Williams Bros Corporation of America. Toll Free (800) 255-5515. Toll Free Fax (800) 822-5001. Phone (540) 636-4444. Fax (540) 636-4455. Web Site [www.wbdoors.com](http://www.wbdoors.com).
- B. Rapid Manufacturing, 4347 Anderson Highway, Powhatan, Virginia 23139.

Specifier Notes: Consult Williams Brothers for assistance in determining the required access doors for the specific application. Delete access doors not required.

Consult Williams Brothers for additional optional accessories available for the specified access doors.

### 2.2 FIRE-RATED ACCESS DOORS

- A. Fire-Rated Access Doors: WB FR PRE 700 Series Premium Heavy Duty Access Door.
  - 1. UL Listed: 1-hour, "B" Label, 250 degrees F maximum temperature rise in 30 minutes for vertical wall installations. Test file number R-10384N.
  - 2. Warnock Hersey Listed: 1-hour rated for vertical wall assemblies. Test file number 7185.
  - 3. California State Fire Marshall Approval: 2 hour fire-rated wall assembly.
  - 4. Door: 14 gauge steel. Rolled safety edges on inside of door.

5. Frame: 16 gauge steel, 2 ½ inches deep.
6. Insulation: 2 inches thick mineral wool (THERMAFIBER) in between 2 pieces of 22 gauge steel.
7. Hinge: Continuous piano hinge allows opening to 180 degrees. Hinge is on long side of door.
8. Latches: Specially designed Ultra Lock-self-latching keyed cylinder paddle latch (WB 151 key code) opposite hinge.
9. Automatic panel closer on all doors. Vertical position only. Ceiling position has self-assisted closing.
10. Inside panel release on all doors.

Specifier Notes: Specify access door finish. Standard finish is electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish or as a prime coat.

The optional stainless steel finish is available up to and including the 36 inch x 36 inch size. Specify Model WB FR PRE SS 700 Series Heavy Duty Access Door.

11. Finish: [Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.] [Type 304 stainless steel and Type 16 No. 4 satin finish. Brushed and non-brushed] [Zinc-coated.]

Specifier Notes: The following is an option. Delete if not required.

12. Hot smoke seal gasketing for 4 sides.

**B. Fire-Rated Access Doors: WB FRU 810 Series Standard Ultra Access Door.**

1. UL Listed: 1-hour, "B" Label, 250 degrees F maximum temperature rise in 30 minutes, for vertical wall installations. Test file number R-10364.
2. Warnock Hersey Listed: 1 hour rating for combustible floor/ceiling assemblies. 3 hour rating for noncombustible floor/ceiling assemblies. 2 hour fire-rated wall assembly. Test file number WHI-495-PSH-0192.
3. Door: 18 gauge steel.
4. Frame: 16 gauge steel. 2 ½ inches frame depth.
5. Insulation: 2 inches thick mineral wool (THERMAFIBER), contained within door cavity.
6. Hinge: Fully-concealed pivot-rod type hinge allows opening to 140 degrees.
7. Latches: Ultra lock with 151 key assembly, opposite hinge.
8. Automatic panel closer.
9. Inside panel release.

Specifier Notes: Specify access door finish. Standard finish is electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish or as a prime coat.

The optional stainless steel finish is available up to and including the 36 inch x 36 inch size. Specify Model WB FRU 810 Series Standard Ultra Access Door.

10. Finish: [Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.] [Type 304 stainless steel and Type 316 No. 4 satin finish. Brushed and non-brushed] [Zinc-coated.]

Specifier Notes: The following is an option. Delete if not required.

11. Hot smoke seal gasketing for 4 sides.

C. Fire-Rated Access Doors: WB FR 800 Series Standard Access Door.

1. UL Listed: 1-hour, "B" Label, 250 degrees F maximum temperature rise in 30 minutes, for vertical wall installations. Test file number R-10364.
2. Warnock Hersey Listed: 1 hour rating for combustible floor/ceiling assemblies. 3 hour rating for non-combustible floor/ceiling assemblies. 2 hour fire-rated wall assembly.
3. Door: 18 gauge steel.
4. Trim and Return Frame: 16 gauge steel.
5. Insulation: 2 inches thick mineral wool (THERMAFIBER), contained within door cavity.
6. Hinge: Fully-concealed pivot-rod type hinge which allows opening to 140 degrees.
7. Latches: Self-latching direct action lock, opposite hinge. Lock to accept both key and knurled knob.
8. Automatic panel closer.
9. Inside panel release.

Specifier Notes: Specify access door finish. Standard finish is electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish or as a prime coat.

The optional stainless steel finish is available up to and including the 36 inch x 36 inch size. Specify Model WB FRU SS 810 Series Standard Ultra Access Door.

10. Finish: [Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.] [Type 304 stainless steel and Type 316 No. 4 satin finish brushed and non-brushed.] [Zinc-coated.]

Specifier Notes: The following are options. Delete if not required.

11. Mortise cylinder prep.
12. Hot smoke seal gasketing for 4 sides.

D. Fire-Rated Access Doors: WB FR DW 820 Series Standard for Drywall.

1. UL Listed: 1-hour, "B" Label, 250 degrees F maximum temperature rise in 30 minutes, for vertical wall installations. Test file number R-10364.
2. Warnock Hersey Listed: 1 hour rating for combustible floor/ceiling assemblies. Test file number WHI-495-PSH-0191. 3 hour rating for non-combustible floor/ceiling assemblies. Test file number WHI-495-PSH-0192. 2 hour fire-rated wall assembly.
3. Door: 18 gauge steel.
4. Frame: 16 gauge steel. 2 ½ inches deep, with 1 inch wide perforated flange of 24 gauge satin coated galvanized steel for mounting.
5. Insulation: 2 inches thick mineral wool (THERMAFIBER), contained within door cavity.
6. Hinge: Fully-concealed pivot-rod type hinge allows opening to 140 degrees.
7. Latches: Self-latching direct action latch, accepts both key and knurled knob.
8. Automatic panel closer.
9. Inside panel release.

Specifier Notes: Specify access door finish. Standard finish is electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish or as a prime coat.

The optional stainless steel finish is available up to and including the 36 inch x 36 inch size. Specify Model WB FR SS 820 Series Standard for Drywall.

10. Finish: [Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.] [Type 304 stainless steel and Type 316 No. 4 satin finish brushed and non-brushed.] [Zinc-coated.]

Specifier Notes: The following are options. Delete if not required.

11. Mortise Best Lock.
12. Flush (Ultra) lockable paddle latch.
13. Hot smoke seal gasketing for 4 sides.

E. Fire-Rated Access Doors: WB FR PL 830 Series Standard for Plaster.

1. UL Listed: 1-hour, "B" Label, 250 degrees F maximum temperature rise in 30 minutes, for vertical wall installations. Test file number R-10364.
2. Warnock Hersey Listed: 1 hour rating for combustible floor/ceiling assembly. Test file number WHI-495-PSH-0191. 3 hour rating for non-combustible floor/ceiling assembly. Test file number WHI-495-PSH-0192. 2 hour fire-rated wall assembly.
3. Door: 18 gauge steel.
4. Frame: 16 gauge steel. 2 ½ inches deep with 3 inches wide perforated flange of 24 gauge galvanized material for mounting. Space from expanded flange to 1/4 inch safety edge of door will accommodate 1 inch of plaster mud.
5. Insulation: 2 inches thick mineral wool (THERMAFIBER), contained within door cavity.
6. Hinge: Fully-concealed, pivot-rod type hinge allows opening to 140 degrees.
7. Latches: Self-latching direct-action lock, opposite hinge. Lock to accept both key and knurled knob.
8. Automatic panel closer.
9. Inside panel release.

Specifier Notes: Specify access door finish. Standard finish is electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish or as a prime coat.

The optional stainless steel finish door is available up to and including the 24 inch x 36 inch size. Specify Model WB FR PL SS 830 Series Standard for Plaster.

10. Finish: [Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.] [Type 304 stainless steel and Type 316 No. 4 satin finish brushed and non-brushed.] [Zinc-coated.]

Specifier Notes: The following are options. Delete if not required.

11. Flush (Ultra) lockable paddle latch.
12. Mortise cylinder prep.
13. Hot smoke seal gasketing for 4 sides.

- F. Fire-Rated Access Doors: WB FRC 50 Series Ceiling Access Door
1. Warnock Hersey Listed: 1 hour rating for combustible floor/ceiling assemblies. 3 hour rating for non-combustible floor/ceiling assemblies.
  2. Door: 16 gauge steel, recessed pan.
  3. Frame: 16 gauge steel, hat channel configuration.
  4. Insulation: 1/2 inch thick ceramic fibreboard.
  5. Hinge: Full-length semi-concealed piano hinge. Opens 180 degrees. On long side of door.
  6. Latches: Self-latching direct action lock, opposite hinge. Lock to accept both key and knurled knob.

Specifier Notes: The automatic panel closer is furnished on all doors, except the 12 inch x 12 inch and 24 inch x 36 inch sizes with optional metal skin.

7. Automatic Panel Closer: Spring-operated, controlled by pneumatic tube.

Specifier Notes: Specify access door finish. Standard finish is electrostatically-applied, baked white enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish coat.

The optional white baked enamel metal skin is used to cover tile.

8. Finish: [Electrostatically-applied, baked white enamel coat over rust-inhibiting phosphate treated steel.] [White baked enamel metal skin.]

## 2.3 GENERAL PURPOSE ACCESS DOORS

A. Access Doors: WB-GP Premium General Purpose Access Door.

1. Door and Trim: 14 gauge steel. Trim 1-1/2 inches wide.
2. Return Frame: 18 gauge steel. Depth 1-3/4 inches.
3. Hinges: Fully-concealed. Opens 170 degrees. On long side of door. Number of hinges varies with size of door.
4. Latches: Flush, stainless steel cam-operated with screwdriver. Positioned opposite hinge and at top and bottom on larger sizes.

Specifier Notes: Specify access door finish. Delete finishes not required. Standard finish is electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish or as a prime coat.

5. Finish: [Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.] [White baked enamel.] [Type 304 stainless steel, No. 4 satin finish.] [Zinc-coated.]

Specifier Notes: The following are options. Delete if not required.

6. Masonry Anchor Straps: Minimum of 4 straps per door.
7. Cylinder Lock: Keyed alike with 2 keys per lock.
8. Mortise Series Lock: Prepped to accommodate lock.
9. Screws: Tamper-proof.
10. Gaskets: Weather-resistant and air-tight neoprene gaskets.

- B. Access Doors: WB-UAD Utility Access Door.
1. Door and Trim: 16 gauge steel. Trim 1-1/2 inches wide.
  2. Return Frame: 16 gauge steel. Depth 1-1/4 inches.
  3. Hinge: 1-piece hidden-pivot rod hinge. Opens 170 degrees.
  4. Latches: Flush, stainless steel cam-operated with screwdriver. Positioned opposite hinge and at top and bottom on larger sizes.

Specifier Notes: Specify access door finish. Delete finish not required. Standard finish is electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish or as a prime coat.

5. Finish: [Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.] [Type 304 stainless steel, No. 4 satin finish.]

Specifier Notes: The following is an option. Delete if not required.

6. Cylinder Lock: Keyed alike with 2 keys per lock.

- C. Access Doors: WB-SMP Surface Mounted Access Door.
1. Door and Trim: 14 gauge steel. Trim 1-1/2 inches wide.
  2. Door Stops: 18 gauge steel. On 3 sides of door opening.
  3. Hinge: Full-length semi-concealed piano hinge. Opens 180 degrees. On long side of door.
  4. Latches: Flush, stainless steel cam-operated with screwdriver. Positioned opposite hinge and at top and bottom on larger sizes.

Specifier Notes: Specify access door finish. Delete finish not required. Standard finish is electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish or as a prime coat.

5. Finish: [Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.] [Type 304 stainless steel, No. 4 satin finish.]

Specifier Notes: The following are options. Delete if not required.

6. Cylinder Lock: Keyed alike with 2 keys per lock.
7. Screws: Tamper-proof.

- D. Access Doors: WB-RP Removable Panel Access Door.
1. Door and Trim: 14 gauge steel. Trim 1-1/2 inches wide.
  2. Return Frame: 18 gauge steel. Depth 1-3/4 inches.
  3. Latches: Flush, stainless steel cam-operated with screwdriver. Positioned on all 4 sides.

Specifier Notes: Specify access door finish. Delete finishes not required. Standard finish is electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish or as a prime coat.

4. Finish: [Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.] [White baked enamel.] [Type 304 stainless steel, No. 4 satin finish.]

Specifier Notes: The following are options. Delete if not required.

5. Masonry Anchor Straps: Minimum of 4 straps per door.
6. Cylinder Locks: Minimum of 2 cylinder locks per door. Keyed alike with 2 keys per lock.
7. Screws: Tamper-proof.
8. Gaskets: Weather-resistant and air-tight neoprene gaskets.

## 2.4 ACCESS DOORS FOR PLASTER

### A. Access Doors: WB-PL Metal Access Door for Plaster.

1. Door: 14 gauge steel.
2. Box Return Frame: 16 gauge steel. Expanded flange 3 inches wide of 24 gauge satin coated galvanized steel. Space from expanded flange to 1/4 inch safety edge of door to accommodate 1 inch of plaster.
3. Hinges: Fully-concealed. Opens 170 degrees. On long side of door. Number of hinges varies with size of door.
4. Latches: Flush, stainless steel cam-operated with screwdriver. Positioned opposite hinge and at top and bottom on larger sizes.

Specifier Notes: Specify access door finish. Delete finish not required. Standard finish is electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish or as a prime coat.

5. Finish: [Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.] [Type 304 stainless steel, No. 4 satin finish.]

Specifier Notes: The following are options. Delete if not required.

6. Cylinder Lock: Keyed alike with 2 keys per lock.
7. Screws: Tamper-proof.

### B. Access Doors: WB-AP Access Door Recessed for Plaster.

1. Door: 14 gauge steel. Recessed 1 inch and lined with expanded metal lath.
2. Frame: 16 gauge steel. 24 gauge galvanized casing bead and expanded metal lath surrounding door.
3. Hinge: Full-length, semi-concealed, stainless steel, piano hinge. Opens 180 degrees. On long side of door.
4. Latches: Flush, stainless steel cam-operated with screwdriver. Positioned on door opposite hinge. Welded steel grommet.
5. Finish: Baked white enamel over rust-inhibiting phosphate treated steel.

Specifier Notes: The following is an option. Delete if not required.

6. Cylinder Lock: Key-operated medium barrel.

## 2.5 ACCESS DOORS FOR DRYWALL



- A. Access Doors: WB-DW Metal Access Door for Drywall.
1. Door: 14 gauge steel.
  2. Return Frame: 16 gauge steel. Perforated flange 1 inch wide of 24 gauge satin coated galvanized steel for mounting.
  3. Hinges: Fully-concealed. Opens 170 degrees. On long side of door. Number of hinges varies with size of door.
  4. Latches: Flush, stainless steel cam-operated with screwdriver. Positioned opposite hinge and at top and bottom on larger sizes.

Specifier Notes: Specify access door finish. Delete finish not required. Standard finish is electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel. This coating can be used as a finish or as a prime coat.

5. Finish: [Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.] [Type 304 stainless steel, No. 4 satin finish.]

Specifier Notes: The following are options. Delete if not required.

6. Cylinder Lock: Keyed alike with 2 keys per lock.
7. Screws: Tamper-proof.

- B. Access Doors: WB-RDW Metal Access Door Recessed for Drywall.
1. Door: 14 gauge steel. Recessed 1 inch to accept drywall.
  2. Box Return Frame: 16 gauge steel. Perforated flange 1 inch wide of 24 gauge satin coated galvanized steel for mounting.
  3. Hinge: Fully-concealed pivot-type hinge. Opens 110 degrees. On long side of door.
  4. Latches: Flush, stainless steel cam-operated with screwdriver. Positioned opposite hinge and at top and bottom on larger sizes.

Specifier Notes: Specify access door finish. Delete finish not required. Standard finish is baked grey enamel coat over rust-inhibiting phosphate treated steel.

5. Finish: [Baked grey enamel coat over rust-inhibiting phosphate treated steel.] [Type 304 stainless steel, No. 4 satin finish.]

Specifier Notes: The following is an option. Delete if not required.

6. Cylinder Lock: Key-operated medium barrel.

## 2.6 ACCESS DOORS FOR ACOUSTICAL TILE

- A. Access Doors: WB-AT Metal Access Door for Acoustical Tile.
1. Door and Trim: 14 gauge steel. Recessed to accept a maximum of 1 inch thick acoustical tile.
  2. Frame: 16 gauge steel.
  3. Hinge: Full-length semi-concealed piano hinge. Opens 180 degrees. On long side of door.
  4. Latches: Flush, stainless steel cam-operated with screwdriver. Positioned opposite hinge and at top and bottom on larger sizes.
  5. Finish: Baked white enamel coat over rust-inhibiting phosphate treated steel.

Specifier Notes: The following is an option. Delete if not required.

6. Cylinder Lock: Key-operated medium barrel.
- B. Access Doors: WB-ATR Fire-Resistive Ceiling Access Door.
1. Door: 16 gauge steel. Recessed 1-1/2 inches.
  2. Frame: 16 gauge steel. Hat channel shape.
  3. Hinge: Full-length semi-concealed piano hinge. Opens 180 degrees. On long side of door.
  4. Latches: Flush, stainless steel cam-operated with screwdriver. Positioned opposite hinge.

Specifier Notes: The following finish can be used as a finish or as a prime coat.

5. Finish: Electrostatically-applied, baked white enamel coat over rust-inhibiting phosphate treated steel.

Specifier Notes: The following is an option. Delete if not required.

6. Cylinder Lock: Key-operated medium barrel.

## 2.7 SECURITY ACCESS DOORS

- A. Access Doors: WB-Medium Security Door.
1. Door: 12 gauge steel.
  2. Frame: 16 gauge steel.
  3. Hinge: Full-length semi-concealed piano hinge. Opens 180 degrees.
  4. Anchors: Heavy steel, welded to frame.
  5. Lock: 1/4-20 theft proof, security bolt, countersunk.
  6. Finish: Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.
- B. Access Doors: WB-High Security Door.
1. Door: 10 gauge steel.
  2. Frame: 2 inch x 2 inch x 3/16 inch angle.
  3. Hinges: Heavy-duty detention butt hinges welded to surround and door. Opens 180 degrees. Minimum of 2 hinges per door. Maximum of 4 hinges per door for larger doors.
  4. Anchors: Heavy steel, welded to frame.
  5. Lock: Prepped for detention lock.
  6. Finish: Electrostatically-applied, baked grey enamel coat over rust-inhibiting phosphate treated steel.

## 2.8 SPECIAL USE ACCESS DOORS

Specifier Notes: Specify Model WBTF-DC or WBTF-HD. Delete model number not required. Add suffix "F" to model number for fiberglass duct.

Consult Williams Brothers for assistance in determining the required model for the specific application.

- A. Access Doors: [WBTF-DC] [WBTF-HD] True Fit Duct Access Door.
  - 1. Door: 24 gauge steel, die-formed.
  - 2. Frame: 22 gauge steel, die-formed, flanged.
  - 3. Insulation: 1 inch thick fiberglass.
  - 4. Edges: Notched, knock-over.
  - 5. Camlock Fasteners: Plated steel.
  - 6. Gaskets: Positive seal gaskets, 1/4 inch thick, 1/2 inch wide.
  - 7. Finish: Mill galvanized.

Specifier Notes: Specify safety retaining chain for Model WBTF-DC. Specify full-length steel hinge for Model WBTF-HD.

- 8. Safety retaining chain.
- 9. Full-length steel hinge.

- B. Access Doors: WB-MAP Plastic Access Door.
  - 1. Door: High impact ABS plastic with UV stabilizers. Removable panel. Locked to return frame with snap friction catch.
  - 2. Frame: High impact ABS plastic with UV stabilizers.
  - 3. Finish: White textured finish.

## **PART 3 EXECUTION**

### **3.1 EXAMINATION**

- A. Examine areas to receive access doors. Notify Architect if areas are not acceptable. Do not begin installation until unacceptable conditions have been corrected.

### **3.2 INSTALLATION**

- A. Install access doors in accordance with manufacturer's instructions at locations indicated on the drawings.
- B. Install access doors plumb, level, square, rigid, without warp or rack.
- C. Provide proper support for frames.
- D. Anchor frames securely in place.
- E. Use manufacturer's supplied hardware.
- F. Replace defective or damaged doors or other components as directed by Architect.

### **3.3 ADJUSTING**

- A. Adjust access doors and latches for smooth operation without binding.
- B. Inspect and adjust locks to operate properly.
- C. Touch-up marred finishes with manufacturer supplied paint.

### **3.4 CLEANING**

- A. Clean surfaces in accordance with manufacturer's instructions.
- B. Do not use abrasive cleaners.

### **3.5 PROTECTION**

- A. Protect access doors and finish from damage during construction.

**END OF SECTION**