

# Standard Backer Rod Closed Cell Polyethylene Foam

Standard backer rod is an ideal non-absorbent compressible backup material. It can be inserted into a joint to control sealant depth to create a backstop to:

- Allow proper sealant tooling
- Allow proper wetting of the joint surfaces
- Yield a proper bond breaker between backer rod and sealant

## Details

### USES

Glazing installations  
Window and door applications  
Expansion joints  
Curtain wall joints  
Partitions  
Log construction  
Pavement joints  
Repairs  
Pre-cast units  
Copings

### COMPATIBILITY

Standard backer rod is compatible with butyl, polysulfide, acrylic polyurethane, silicone, and most other cold applied sealants.

### CONTACT US

P: 800.521.9594 or 248.643.6400 E: [wilpro@williamsproducts.net](mailto:wilpro@williamsproducts.net)

## Typical Physical Properties

DIAMETER	SHIPPING FORMAT	FEET PER CARTON	METRIC DIAMETER	METERS PER CARTON
1/4"	2 spools	4000	6 mm	1219
3/8"	1 spool	2100	9 mm	640
1/2"	2 spools	2500	12 mm	762
5/8"	2 spools	1550	15 mm	472
3/4"	1 spool	1100	19 mm	335
7/8"	1 spool	850	22 mm	259
1"	1 spool	600	25 mm	182
1-1/2"	6' lengths	396	38 mm	121
2"	6' lengths	228	50 mm	70
2-1/2"	6' lengths	144	63 mm	44
3"	6' lengths	102	76 mm	31

DIAMETER SHIPPING FORMAT FEET PER CARTON			METRIC DIAMETER METERS PER CARTON	
4"	6' lengths	48	101 mm	15
5"	6' lengths	90	127 mm	27
6"	6' lengths	60	152 mm	18

\* Sizes 2-1/2" to 6" available in white only.

\* Rectangular cartons with convenient hand holes for carrying, are ideal for warehousing and handling

\* UPS and most other express services will accept all cartons except 5" & 6"

\* Truckload quantities furnished on pallets and may be warehoused 2 pallets high to maximize space