

## Williams Products, Inc

1750 Maplelawn Trou, Ml. 48084 Toll Free: 800-521-9594 Phone: 248-643-6400

Fox: 248-643-7117

# **Product Index**DIVISION 3 CONCRETE

**Bearing Pads** 

Com-Pad 100 Masticated Rubber

Bear-Pad 200 Cross Laminated with oriented fibers
Fab-Pad 300 Laminated, rubber and ductile fabric
1200 Series Commercial Grade Dense Neoprene

AASHTO Grade Neoprene Conforms to AASHTO requirements, 2500 PSI tensile strength

**Rubber Waterstop** 

Compounds Neoprene, Styrene-Butadiene-Rubber(SBR)

Sizes(widths) 6" & 9"

Profiles Dumbbell(DB) and Centerbulb(CB)

## Rubber "J" Gate Seals

Hi Tensile Neoprene Williams Compound # 1025

**Expansion Joints** 

Econ-O-Foam CCPE

EJ-2000 XL Polyolifin

NN-1, 1040 Series Closed Cell Neoprene

1300 Series Concrete Gray Sponge Rubber

1400 Series Open Cell Neoprene (Vibration Isolation)

1752 Highway Modified Isomeric Polyolefin Resilient Flexible Gray Foam.

Expand-O-Foam - 900 Closed Cell Polyethelene Foam, ASTM D-3575 & ASTM D-1056

(Modified).

Everlastic® MPP 100 Proplastic Isotropic Polyolefin Resilient Molded Foam, White in color.

#### **DIVISION 4 MASONRY**

Column Isolation

Column Boxboard Coated Corrugated

Econ-O-Foam CCPE

EJ-2000 XL Polyolifin

#### **CMU Control Joints (Vertical)**

Slot Seal Standard, Wide Flange, Block Seal Hard rubber cross shape, shear keys in sash blocks



Pg. 1 of 3

We do not guarantee the applicability or accuracy of this information or the suitability of our products for any given situation. The products discussed are sold without warranty, expressed or implied. Buyer assumes all responsibility for any loss or damage arising from the handling or use of our products, whether done in accordance with directions or not. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent.



## Williams Products, Inc

1750 Maplelawn Troy, Ml. 48084 Toll Free: 800-521-9594 Phone: 248-643-6400

Fox: 248-643-7117

## Weathertite R, Everlastic® M-CJ

Compressible Filler to seal Michigan Control Joints

Econ-O-Foam for Bond Break in core Compressible to accommodate movement

## **CMU Expansion Joint (Horizontal)**

Fill gap at top of wall Expand-O-Foam EVA 200G

### Air Seal Gasket

1056 Joint Filler

## **Partition Closures**

Close off gap between wall and deck (flat or fluted)
Special Fabrications
EVA 200
EPDM, 3000 Series
Fire Rated
Dyna Shield Ceramic Fiber Joint Filler

## Vapor Barrier

MWM-40 Masonry Wall Membrane

## **Flashing**

MF-40
Self Stick, Rubberized Asphalt
EPDM Membrane
Available by special order
Neoprene Membrane
Available by special order
PVC
10 mil to 56 mil
Available by special order





## Williams Products, Inc

1750 Maplelawn Troy, Ml. 48084 Toll Free: 800-521-9594 Phone: 248-643-6400

Fax: 248-643-7117

## **Anchor Gaskets**

Self-stick, CC Neoprene Thermal and moisture break behind anchors

### **Brick Expansion Joints**

Neo Seal IV
Neoprene profile allows maximum movement

#### M-CJ

Self-stick, CC Rubber Joint Filler

## **Econ-O-Foam**

Filler is inherent bond breaker for most sealants

## **Coping Gaskets**

Special shapes Variety of Materials

### **Brick Vents**

Williams-Goodco PVC Brick Vents Ventilates and equalizes pressure within cavity Sizes, 2 - 1/4", 2 - 3/4", 3 - 5/8" Colors, Standard Gray, We can dye to match mortar color

