

Contact: **1-800-872-5625**

Dow Froth-Pak 210 Class A Foam Insulation

Product #: W-FP210CA

Dow Froth-Pak 210 Class A Foam Insulation Kit, is a two-component, quick-cure, fire-rated polyurethane spray foam system ideal for insulating large open interior or exterior cavities. Foam will skin over in 30-40 seconds and be completely cured in under 1 minute. It can be exposed in roof and wall junctures up to 6in in height, 2in in depth, and unlimited length. Used behind a thermal barrier to qualify as an effective insulation for:

- Stud wall cavities
- Cold floors above unheated areas
- Rim and band joist
- Crawl space walls and ceilings
- Attic ductwork
- Plumbing wall pipe insulation and support

Offers coverage of 210 bfm/17.5 cuft.

People Also Purchased

DMS Industrial Rasp Paper Sheets, Adhesive Backed, 16

Product #: I-RPA2

\$24.40

Marshalltown Stucco Rub Brick

Product #: T-RB6

\$18.65

Contact: **1-800-872-5625****Dow Froth-Pak Spray Foam
Caulking Nozzle - 25-Pack**

Product #: WFPNCKL

\$38.15**G-Saw 17 tpi folding Handle**

Product #: W.TJGSAW

\$26.99**More Info**

Froth-Pak 210 Kit includes:

- Part A Tank - Isocyanate
- Part B Tank - Polyol
- INSTA-FLO Gun Dispenser & Hose Assembly with 9 ft hose
- Anti-Crossover Spray Nozzles (6 cone nozzles, 4 fan nozzles)
- 1 Petroleum Jelly Packet (5 g)
- 1 Operation Instruction Manual

Product Specs**Expansion Ratio:** 2-4:1**Coverage:** 210 board ft.**Insulation Value:** R Value 6.6 initial, 5.6 cured**Cure Time:** 1 Minute**Application Temp:** 40 – 100 Degrees F**Color:** Cream**Compatible Material:** Wood, Glass, Metal, Most Plastics**Standards:** UL Classified**[Click here for the Safety Data Sheet on this product.](#)**