



# Great Stuff™ Pro

## Window & Door Foam Sealant



Building and construction professionals throughout North America prefer Great Stuff Pro Window and Door insulating foam sealant over other choices for filling and air-sealing the gap between a window or door and its rough opening.

### PRODUCT FEATURES

- ▶ Low pressure formula
- ▶ Flexible seal permits expansion and contraction
- ▶ Bonds to all window types
- ▶ Controllable bead size
- ▶ Quick cure and trim
- ▶ One can = 13 quart tubes of caulk



### GREAT STUFF PRO ADVANTAGES

- Low pressure formulation will not distort or bow window and door frames
- Soft, pliable yellow foam is easy to push and re-position if gap is overfilled
- Eliminates unwanted and uncontrolled air flow
- Forms a durable, airtight, water-resistant bond
- Conforms to ASTM E-06/ASTM E-2112 standards for installation of exterior windows, door and skylights
- Improves insulation value



1055 Leiscz's Bridge Road • Leesport, PA 19533  
610-926-6815 • 1-800-872-5625 • Fax: 1-800-854-6614  
[www.wind-lock.com](http://www.wind-lock.com)



# Great Stuff™ Pro

## Window & Door Foam Sealant

### PRODUCT DESCRIPTION

Great Stuff Pro is a one-component, multipurpose, low-expansion construction filler.

### APPLICATIONS

Filling, sealing and insulating of joints, voids, and cavities around windows and doors.

### INSTALLATION

Read all instructions and safety information (MSDS) before using any product. Foam bonds to skin quickly — wear gloves, eye protection and work clothes during application. Use drop cloths.

**Surface Preparation:** Surface should be free of oil, grease and excess moisture.

**Application:** Great Stuff Pro is applied with a gun applicator at the junction of the plate line and the slab or foundation, any penetration through the top or the bottom of the plate line, around window and door frames, cracks and holes in the exterior sheathing from penetration made for utility services, corner and T-wall intersections, and any other place where air might penetrate the exterior envelope.

**Storage:** Store in cool dry area in upright position.

**Limitations:** Great Stuff Pro professional foam should not be left permanently exposed to ultraviolet light.

### DOW GREAT STUFF PRO TECHNICAL DATA

Property	Test Method	Window & Door
Basis	—	MDI monomer, polyurethane resin propane/isobutene
Characteristics	—	Flexible — Cushion like
UL Classified (Class 1)	ASTM E-84	Flame Spread 10/Smoke Developed 20
Color	—	Yellow
Density	ASTM D-1622	1.63
Thermal Resistance (R Value)	ASTM C-518	3.8
Percent Closed Cell Content	ASTM D-2856	<38.37
Application Temperature	—	40°F to 90°F
Storage Temperature	—	Up to 120°F
Service Temperature	—	-200°F to +200°F
Shelf Life	—	18 months
Tack Free Time	—	8 minutes
Cure time	—	8 hours
Cutting time	—	2 hours
<b>Yield 24 oz can</b>	<b>Bead Size</b>	<b>Linear Feet</b>
	3/8"	1000

### ORDERING INFORMATION

#### Great Stuff Pro—Window & Door

**PART CODE:** W-GSWD (Case of 12 cans, Gun Foam)  
W-GSTWD (Case of 12 cans, Straw Foam)



Distributed by: