



PERMALATH® GLASS FIBER LATH FOR STUCCO AND STONE

*Now Available to
Everyone, Nationally
Through Wind-lock®.*

PermaLath® is an open weave, corrosion-free, three-dimensional, self-furring, glass fiber reinforcing lath.

FEATURES AND BENEFITS

Non Metallic

Will not rust; ideal for coastal applications

Pliable, with No Sharp Edges

Safer and easier to cut and handle

Non-Directional

Can be applied vertically or horizontally

Wide Rolls

Fewer overlaps required to give better coverage

Three-Dimensional Profile

Self-furring, excellent mechanical key using traditional fastening procedures

Low Profile on Overlaps

Overlaps are easily feathered, eliminating shadowing

Alkali Resistant

Long-term durability and performance

Packaged in Lightweight Rolls

Application time/labor savings/storage

PermaLath® Glass Fiber Lath

PermaLath® is a nominal 1/8" thick glass fiber reinforcing lath designed for use with cementitious exterior wall coatings manufactured in accordance with ICC-ES AC-11 at a maximum thickness of 3/8" to 1/2". PermaLath® provides keying and continuous reinforcement for stucco used on vertical wall applications with solid backing.

Part Code	Qty	Size	Description	Contr Price	Approx Wt
I-PL	1 Roll	39" x 150'	1/8" Fiberglass Lath 487.5 sq ft	CALL	16 lb

*Note: 20 Rolls per Skid 39" x 150', 1/8" Fiberglass Lath
9,750 sq ft, 375 lb per skid.*

PermaLath® 1000 Glass Fiber Lath

PermaLath® 1000 is a nominal 1/4" thick glass fiber reinforcing lath designed for use with cementitious exterior wall coatings (traditional stucco) at a maximum thickness of 1/2" to 7/8". PermaLath® 1000 can also be used as a mortar base for lightweight veneer facing, such as stone veneer.

Part Code	Qty	Size	Description	Contr Price	Approx Wt
I-PL1000	1 Roll	39" x 150'	1/4" Fiberglass Lath 487.5 sq ft	CALL	31 lb

*Note: 8 Rolls per Skid 39" x 150', 1/4" Fiberglass Lath
3,900 sq ft, 303 lb per skid.*