

Contact: **1-800-872-5625**

Rex Wrap Fortis Housewrap

Product #: W-REXWPHP

REX WRAP FORTIS prevents the infiltration of air and water while allowing for the escape of water vapor. Rex Wrap Fortis features the unique ALTA 360 Drainage Technology that can drain in EVERY direction and works with wood, vinyl, metal, brick, stone, cement sidings, stucco or EIFS. Rex Wrap Fortis offers a one-of-a-kind weather protection layer for any type of construction.

- Comes in High-P and Low-P for different climates (see specifications below for details)
- 360 Degree Drainage Technology
- Reduced Waste, simplified installation
- 5 ft x 200 ft roll sizes

People Also Purchased

3M 1-7/8in x 55yd Red Construction Seaming Tape

Product #: W-3M8087CW

\$14.99

Dow Corning 790 Silicone Building Sealant

Product #: W-DCGR

\$125.08

Contact: **1-800-872-5625****Dow Weathermate Straight
Flashing 18in x 100ft**

Product #: WDSF18

\$145.00**Dow Weathermate Straight
Flashing**

Product #: WDSF4

\$37.73**More Info****Product Specifications**

	Low-P	High-P	Test Method
Air Penetration Resistance	0.0013	0.00082	ASTM E2178 (cfm/ft2@1.57 psf)
	>2000	>2500	Gurley Hill (TAPP-T460 (sec/100cm)
Water Vapor Transmission	105	385	ASTM E96 Method A (g/m2/24 hrs)
	15	55	(perms)
	72	465	ASTM E96 Method B (g/m2/24 hrs)
	10.4	67	(perms)
Water Penetration Resistance	>300	>300	AATCC 127 (cm)
Basis Weight	2.2	2.2	TAPPI T-410 (oz/sq yd)
Thickness	8	8	ASTM D3776 (mils)
Breaking Strength	30	30	ASTM D5034 (lb/in) MD
Dry Tensile	45	45	ASTM D5034 (lb/in)MD
Tear Resistance (Trapezoid)	13.5	13.5	ASTM D1117 (lbs)MD
	12.5	12.5	ASTM D1117 (lbs)CD
Drainage Efficiency	>95%	>95%	ASTM E2273
	>95	>95%	ICC-ES AC 235 Section 4.5
Surface Burning Characteristics	5 Class A	5 Class A	ASTM E85 Flame Spread Index
	45 Class A	45 Class A	Smoke Develop Index
Ultra Violet Light Exposure	180 Days	180 Days	