



OTHER FASTENERS



1. ULP-302 Series Selection

The ULP-302 and ULP-402 are engineered to attach PermaLath® 17, 20 gauge stucco netting, as well as 2.5 and 3.4 metal lath (hard coat stucco systems). NOT for use with PB EIFS. For standard PB applications with the thermal recessed chamber, refer to Wind-Devil® 2 and Long-lock fasteners.

Engineered Features

- 1-3/4" diameter
- Made of high-grade polypropylene plastic
- Unique design allows plate to flatten out in application
- Large ribs stiffen plate, limit deflection
- 16 keyholes allow for mechanical locking of base coat
- Can be screw fastened, nailed or shot
- Engineered "flash" allows for pre-assembly of screw fasteners

Consult system manufacturer for specific requirements.

Wood/Lite Metal Series

Part Code	Qty/Box	Insulation Thickness	Screw Size	Approx Wt/Box
ULP-3WLM1	1000	3/4"	#7 x 1-5/8"	13 lb
ULP-3WLM2	1000	1"	#8 x 2"	15 lb
ULP-3WLM3	1000	1-1/2"	#8 x 2-1/2"	17 lb
ULP-3WLM4	1000	2"	#8 x 3"	19 lb
ULP-3WLM5	1000	3"	#8 x 4"	21 lb

Steel Series

Part Code	Qty/Box	Insulation Thickness	Screw Size	Approx Wt/Box
ULP-3S1	1000	3/4"	#6 x 1-5/8"	12 lb
ULP-3S2	1000	1"	#6 x 2"	14 lb
ULP-3S3	1000	1-1/2"	#8 x 2-5/8"	18 lb
ULP-3S4	1000	2"	#8 x 3"	19 lb
ULP-3S5	1000	3"	#10 x 4"	27 lb

2. ULP-302 Plate

Part Code	Qty/Box	Description	Approx Wt/Box
ULP-302	1000	Plates	6 lb

3. ULP-402 Series Selection

Engineered Features

- 1-3/4" diameter
- Made of high-grade polypropylene plastic
- Pre-spotting central stem/tab allows for quick and easy pre-spotting into insulation board
- Large ribs stiffen plate, limit deflection
- 16 keyholes allow for mechanical locking of base coat
- The ULP-402 is unassembled and can be utilized with Wind-lock® highly coated exterior fasteners

Consult system manufacturer for specific requirements.

Part Code	Qty/Box	Approx Wt/Box
ULP-402	1000	6 lb

4. Long-lock Fasteners

Use these for all of your thick foam fastening needs, such as: cornice details, arches, columns, custom parapet shapes and quoins. All fasteners come fully assembled.

Engineered Features

- 1-3/4" diameter
- Finger closure and recessed fastener chamber
- Utilized for thicker insulation

Consult system manufacturer for specific requirements.

WLM—Wood/Lite Metal/Masonry Screws

Hardness of masonry varies and may require a non-standard drill bit. Please consult Wind-lock® for assistance in proper drill bit size. Includes one drill bit per 200 pieces.

Part Code	Qty/Box	Insulation Thickness	Screw Size	Approx Wt/Box
WLM-7	100	4"	#14 x 5"	5 lb
WLM-8	100	5"	#14 x 6"	5 lb
WLM-9	100	6"	#14 x 7"	6 lb
WLM-10	100	7"	#14 x 8"	7 lb
WLM-11	100	8"	#14 x 9"	8 lb
WLM-12	100	9"	#14 x 10"	8 lb
WLM-13	100	10"	#14 x 11"	9 lb
WLM-14	100	11"	#14 x 12"	10 lb
WLM-15	100	12"–13"	#14 x 14"	12 lb

For even longer fasteners, please contact Wind-lock®



Stock to Dock Shipping Guarantee

Products highlighted in yellow are guaranteed to ship within 24 hours or freight costs are **FREE!** Larger orders may require additional lead times. Call for details.