


PRODUCT SUBMITTAL

WIRE-BOND

#1801 Double Eye



MATERIAL CONFORMANCE

ASTM A1064/A1064M - (Cold drawn steel wire)

Tensile Strength - 80,000 psi

Yield Point - 70,000 psi

ACI / ASCE 530 - (Building code requirements for masonry structures)

Mill Galvanized / Zinc Coating: **ASTM A641 / A641M (0.10 Oz per sq ft)**

Hot Dip Galvanized after fabrication / Zinc Coating

ASTM A153 / A153M-B2 (1.50 oz per sq ft)

Stainless Steel **ASTM 580 / ASTM 580M Type 304** (Type 316 available on special order)

Recycled Content:

Mill Galvanized & Hot Dipped,
82.8% Post-Consumer
17% Post Industrial / Pre-Consumer,

Stainless Steel,
60% Post Consumer
V O C Content - 0%

SIZES / FINISHES

#1801 Double Eye: 2-1/2" wide, 3/16" Diameter Standard

Length: 2-3/4" 3" 3-1/2"

4" 4-1/2"

4-3/4" 5-3/4"

FINISH:

Mill Galvanized

Hot Dip Galvanized

Stainless Steel



Corporate Office: 400 Rountree Rd Charlotte, NC 28217
TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224

WIRE-BOND

www.wirebond.com

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113
TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113