

PRODUCT SUBMITTAL

WIRE-BOND

3612 Grout Stop



Grout Stop is designed to prevent grout from falling through block core while maintaining a positive bond in mortar joint.

Constructed of strong, non-corrosive 1/4" square polypropylene monofilament screening

Provides improved bonding of masonry anchor in hollow block construction

SIZES			
100 feet per roll			
Width:	2" for 4" CMU	4" for 6" CMU	6" for 8" CMU
	8" for 10" CMU	10" for 12" CMU	

TECHNICAL DATA

Characteristic	UOM	Average Value	Test Method
Weight	g/m2	32.7	N/A
Tensile M.D.	lbs/inch	11.22	ASTM D5034
Tensile M.D.	%	24.67	ASTM D5034
Tensile C.D.	lbs/inch	11.46	ASTM D5034
Tensile C.D.	%	25.37	ASTM D5034
Mesh Size	mm	appr. 6x6	N/A
Typical Range +/- 10%			

The above information is given for informational purposes only

The properties and values presented herein are to be considered only typical and not binding

Corporate Office: 400 Rountree Rd Charlotte, NC 28217
TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224



www.wirebond.com

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113
TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113