



Control Joint Installation Instructions

- A. Control joints are typically located at wall openings.
- B. Changes in wall height or thickness.
- C. Construction joints in foundations, roofs and floors.
- D. Wall intersections.
- E. Distance not over ½ the allowable joint spacing from all corners.
- F. A determined spacing for the length of the wall.
- G. For walls without openings, control joints are used to divide wall into a series of isolated panels.

CONTROL JOINT SPACING AS FOLLOWS

RECOMMENDED SPACING OF CONTROL JOINTS	VERTICAL SPACING OF JOINT REINFORCEMENT			
	NONE	24"	16"	8"
RATIO OF PANEL LENGTH (L) TO HEIGHT (H) L/H	2	2 ½	3	4
MAX. PANEL HEIGHT	40'	45'	50'	60'

INSTALLATION

- A. No Special installation specifications are required for the products beyond what what would normally appear in a Concrete Unit Masonry Specification.

PREPARATION

- A. Position WIRE-BOND Masonry Control Joint in concrete unit masonry Specifications.
- B. Inspect WIRE-BOND Masonry Control Joint to be sure they are free of dirt and surface contaminants.

DELIVERY, STORAGE AND HANDLING

- A. Store WIRE-BOND Masonry Control Joint in its original package away from moisture.
- B. If WIRE-BOND Masonry Control Joint is out of its shipping packages the joint material should be protected from sunlight, dirt, oil and contaminants.

Corporate Office: 400 Rountree Rd Charlotte, NC 28217
TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224



Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113
TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113