


PRODUCT SUBMITTAL

WIRE-BOND

2401 RJ-711 Seismic (Plastic)



MATERIAL CONFORMANCE

SIZES / FINISHES

ASTM A1064 / A1064M - (Cold drawn steel wire)
Tensile Strength - 80,000 psi
Yield Point - 70,000 psi

ACI / ASCE 530 - (Building code requirements for masonry structures)

SHEET METAL - (Carbon Steel) **ASTM A1008 / A1008M**
Mill Galvanized / Zinc Coating: **ASTM A641 / A641M (0.10 Oz per sq ft)**
Hot Dip Galvanized after fabrication / Zinc Coating
ASTM A153 / A153M-B2 (1.50 oz per sq ft)

Stainless Steel **ASTM 580 / ASTM 580M Type 304** (Type 316 available on special order)

2401 RJ711:
 14 gauge 12 gauge

2402 Hook: 3/16" Diameter Standard
 3-1/4" 4-1/4" 5-1/4" Other _____

INSULATION

0	1"	1-1/2"	2"	2-1/2"	3"
3-1/2"	4"				

Straight & Cut Seismic Wire:
9 gauge 3/16"



FINISH:
 Mill Galvanized
 Hot Dip Galvanized
 Stainless Steel

Corporate Office: 400 Rountree Rd Charlotte, NC 28217
TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224



www.wirebond.com

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113
TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113