


PRODUCT SUBMITTAL



3000Z Rigid Steel Tie



For anchoring load bearing walls at intersection

MATERIAL CONFORMANCE	SIZES / FINISHES									
<p>SHEET METAL - (Carbon Steel) ASTM A1008 / A1008M</p> <p>Mill Galvanized / Zinc Coating: ASTM A641 / A641M (0.10 Oz per sq ft)</p> <p>Hot Dip Galvanized after fabrication / Zinc Coating ASTM A153 / A153M-B2 (1.50 oz per sq ft)</p> <p>Stainless Steel ASTM 580 / ASTM 580M Type 304 (Type 316 available on special order)</p> <div style="display: flex; align-items: center; margin-top: 20px;">  <p>Recycled Content: Mill Galvanized & Hot Dipped, 82.8% Post-Consumer 17% Post Industrial / Pre-Consumer, Stainless Steel, 60% Post Consumer V O C Content - 0%</p> </div>	<p>Standard Size: 1/4" x 1-1/2" x 24" with 2" bends</p> <p>Custom Size:</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 33%;">Thickness:</td> <td style="width: 33%;">1/8"</td> <td style="width: 33%;">1/4"</td> </tr> <tr> <td>Width:</td> <td>Length:</td> <td>Bends:</td> </tr> </table> <p>FINISH:</p> <table style="width: 100%; border: none; margin-top: 10px;"> <tr> <td style="width: 33%;">Mill Galvanized</td> <td style="width: 33%;">Hot Dip Galvanized</td> <td style="width: 33%;">Stainless Steel</td> </tr> </table>	Thickness:	1/8"	1/4"	Width:	Length:	Bends:	Mill Galvanized	Hot Dip Galvanized	Stainless Steel
Thickness:	1/8"	1/4"								
Width:	Length:	Bends:								
Mill Galvanized	Hot Dip Galvanized	Stainless Steel								

Corporate Office: 400 Rountree Rd Charlotte, NC 28217
TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224



www.wirebond.com

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113
TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113