

PRODUCT SUBMITTAL



Dc`na Yf Screw



DESCRIPTION / MATERIAL CONFORMANCE

Dc`na Yf Screw:

- The maximum in corrosion resistant coatings.
- Average of 30 cycles of corrosion resistance.
- Provides long-term corrosion protection.
- Compatible with painted or metal surfaces.
- Out performs existing mechanical and electro-platings.
- Does not promote corrosion that can be caused by electro-chemical reaction between dissimilar metals.

ASTM - C954

8 UfVt 7 cUfjb[`XYg[[bYX'tc`gi gHUb`ASTM - B117`%\$\$\$` ci fg

SIZES / FINISHES

Sizes:

#10 x 1-1/2"

#12 x 2"

#12 x 3"

#12 x 4"

9/16" EPDM Washer :

yes

no



Corporate Office: 400 Rountree Rd Charlotte, NC 28217
TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224



www.wirebond.com

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113
TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113