

PRODUCT SUBMITTAL

WIRE-BOND


4200 Termination Bar



Termination Bar



Flashing

MATERIAL CONFORMANCE	SIZES / FINISHES
<p>SHEET METAL:</p> <p>Stainless Steel Type 304: ASTM A240/A240M, ASTM 666, ASTM A480/A480M (Type 316 available on special orders)</p> <p>Aluminum: ASTM B221 / ASTM B221M</p>  <p>Steel Products (flats) Recycled Content: Stainless Steel, 60% Post Consumer Aluminum 18% average (10% - 25% Range) Post Consumer 56% average (25% - 75% Range) Pre Consumer</p> <p>V O C Content - 0%</p>	<p>#4200 Termination Bar:</p> <p>Stainless Steel: 1/8" x 1" wide x 10'-0"</p> <p>5/16" Slotted holes: 16" O.C. 8" O.C. 6" O.C.</p> <p>Aluminum: 1/8" x 1" wide x 10'-0"</p> <p>3/8" Slotted holes: 16" O.C. 8" O.C.</p>

Corporate Office: 400 Rountree Rd Charlotte, NC 28217
 TEL: (800) 849-6722 FAX: (704) 525-3761

Mailing Address: P.O. Box 240988 Charlotte, NC 28224



www.wirebond.com

Memphis Plant: 2365 Harbor Ave. Memphis, TN 38113
 TEL: (800) 441-8359 FAX: (901) 775-9449

Mailing Address: P.O. Box 13124 Memphis, TN 38113