

SAFETY DATA SHEET

Page 1 of 2

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product: AIR-SHIELD™ LM Part Number: 6512000

Manufacturer: W. R. MEADOWS, INC. Address: 300 Industrial Drive

Hampshire, Illinois 60140

VCCIII

Telephone: (847) 214-2100 In case of emergency, dial (800) 424-9300 (CHEMTREC)

Revision Date: 3/31/2025

Product Use: Liquid Membrane Air/Vapor and Liquid Moisture Barrier.

SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

HMIS HAZARD STATEMENTS

| Health | | 1 | WARNING!

| Flammability | | 1 | Causes mild skin irritation. (Category 3)

| Reactivity | | 0 | PRECAUTIONARY STATEMENTS

Avoid direct contact.

1		CAS %		SARA	Vapor Pressure	LEL	
ı	Chemical Name:	<u>Number</u>	<u>Weight</u>	<u>313</u>	(mm Hg@20°C)	(@25°C)	
ŀ	1. Petroleum Asphalt	8052-42-4	50-55	No	N/A	N/A	
	2. Petroleum Oil Base Stock	64742-65-0	1-5	No	N/A	0.9	N/A = Not Applicable

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA)

and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush eyes with water for fifteen (15) minutes. If symptoms persist, seek medical attention.

SKIN CONTACT: Wash affected areas with mild soap and water.

INHALATION: Not expected to be an exposure route as supplied. If respiratory symptoms develop, seek medical attention.

INGESTION: Dilute with liquid unless the victim is unconscious or very drowsy. Do not induce vomiting. If vomiting spontaneously

occurs, prevent lung aspiration. Seek immediate medical attention.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC: See Section Eleven for Symptoms/Effects.

SECTION 5: FIRE AND EXPLOSIVES HAZARDS

FLASHPOINT: Product will not flash due to water content. EXTINGUISHING MEDIA: Water fog, foam, dry chemical.

CHEMICAL/COMBUSTION HAZARDS: Oxides and compounds of nitrogen/sulfur, carbon monoxide/dioxide, and incomplete

combustion products.

| Personal Protection |

PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: Avoid smoke inhalation. Use appropriate personal protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Avoid direct contact. Dike and contain spilled material. Remove source of spill if safe to do so. Apply absorbent and place clean-up material in sealed/marked containers for proper disposal. Clean-up materials will be classified as non-hazardous waste.

SECTION 7: HANDLING AND STORAGE

SAFE HANDLING PROCEDURES: Avoid direct contact.
SAFE STORAGE: Prevent product from freezing.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

	ACGIN							
<u>Chemical Name</u> :	<u>PEL</u>	PEL/CEILING	PEL/STEL	<u>SKIN</u>	<u>TLV</u>	TLV/CEILING	TLV/STEL	<u>SKIN</u>
1. Petroleum Asphalt	5 mg/m ³ *	N/E	N/E	No	0.5 mg/m ³ *	N/E	N/E	N/E
2. Petroleum Oil Base Stock	N/E	N/E	N/E	No	5 mg/m ³ +	N/E	N/E	N/E
*: Asphalt Fumes		+: Mineral Oil Mist in Air			N/E: Not Established			

ENGINEERING CONTROLS: None required under normal use conditions.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, chemical-resistant gloves.

SAFETY DATA SHEET

Date of Preparation: 3/31/2025 Page 2 of 2 6512000 **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES BOILING POINT: 212 °F** VAPOR DENSITY: N/A % VOLATILE BY VOLUME: N/A EVAPORATION RATE: <1 (Ether=1) pH LEVEL: N/A % VOLATILE BY WEIGHT: 30 PRODUCT APPEARANCE: Black Liquid WEIGHT PER GALLON: 8.3 VOC CONTENT: 0 g/L MELTING/FREEZING POINT: N/D ODOR: None **ODOR THRESHOLD: N/D** FLASH POINT: See Section 5 FLAMMABILITY: N/D UEL/LEL: N/D VAPOR PRESSURE: N/D **RELATIVE DENSITY: N/D SOLUBILITY: N/D** PARTITION COEFFICENT: N/D **AUTOIGNITION TEMPERATURE: N/D DECOMPOSITION TEMPERATURE: N/D** VISCOSITY: N/D N/A: Not Applicable N/D: Not Determined SECTION 10: STABILITY/REACTIVITY

STABILITY: Stable. HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS AND MATERIALS TO AVOID: None recognized. HAZARDOUS DECOMPOSITION PRODUCTS: None recognized.

SECTION 11: TOXICOLOGICAL INFORMATION

EYE CONTACT: Direct contact may cause mild irritation.

SKIN CONTACT: Direct contact may cause slight skin irritation. Prolonged/repeated contact may result in irritation.

INHALATION: Not anticipated to be an exposure route. **INGESTION:** Not anticipated to be an exposure route.

SIGNS AND SYMPTOMS: Symptoms of eye irritation include tearing, reddening, and swelling. Symptoms of skin irritation include redness and swelling. Gastrointestinal irritation symptoms include nausea, vomiting, and abdominal discomfort. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to this product.

OTHER HEALTH EFFECTS: ACGIH classifies asphalt as Not Classifiable as a Human Carcinogen; A4.

SECTION 12: ECOLOGICAL INFORMATION ECOTOXICITY: N/E **DEGRADABILITY: N/E BIOACCUMULATIVE POTENTIAL: N/E SOIL MOBILITY: N/E** OTHER ADVERSE EFFECTS: None Recognized N/E = Not Established

SECTION 13: WASTE DISPOSAL INFORMATION

WASTE DISPOSAL INFORMATION: Solidified product can be landfill disposed. No free liquids.

SECTION 14: TRANSPORTATION INFORMATION

HAZARDOUS/NON-HAZARDOUS MATERIAL: Not regulated by DOT.

HAZARD CLASS: N/A **PACKING GROUP: N/A** UN NUMBER: None.

UN PROPER SHIPPING NAME: N/A

ENVIRONMENTAL HAZARDS: None recognized. **BULK TRANSPORTATION INFORMATION:** None SPECIAL PRECAUTIONS:

Prevent product from freezing. N/A = Not Applicable**SECTION 15: REGULATORY INFORMATION**

None recognized.

OTHER REGULATORY CONSIDERATIONS:

SECTION 16: OTHER INFORMATION

PREPARATION DATE: 3/31/2025 PREPARED BY: **Dave Carey**

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.