



DECK-O-SEAL®

Polysulfide-Based Joint Sealant



DECK-O-SEAL two-part, polysulfide-based joint sealant is a premium-grade, pourable, self-leveling sealant. It is a non-staining sealant that cures at an ambient temperature to a firm, flexible, tear-resistant rubber. **DECK-O-SEAL** is highly resilient and has excellent recovery characteristics after extended periods of compression or elongation.

DECK-O-SEAL is resistance to most chemicals, to all weather conditions, aging, and shrinkage.

DECK-O-SEAL is used for caulking and sealing joints subject to movement to provide a firm, flexible, weather-tight seal. It is ideal for sealing joints on swimming pool decks. It is applicable for interior and exterior use.

- Highly resilient with excellent recovery characteristics.
- Provides a uniform, watertight seal.
- Prevents uncontrolled cracking by allowing expansion and contraction during temperature changes.
- Stays flexible . . . won't become brittle or crack due to ultraviolet exposure.
- Resists abrasion, weathering, and moisture . . . elevated temperatures will not cause discoloration.
- Not affected by today's pool chemicals.
- Retains joint soundness in service once it's cured and can be stretched or compressed up to 25%
- Available in Dura-White, Stone Gray, Desert Tan (Black, Redwood and custom colors by special order)

COVERAGE (LINEAL FEET)

DEPTH OF JOINT	WIDTH OF JOINT						
	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/4"	231	154	106	92	77	66	58
3/8"		102	77	62	51	44	38
1/2"			58	46	38	33	29
5/8"				37	31	26	23
3/4"					26	22	19
7/8"						19	17
1"							14

DECK-O-SEAL | A Division of W. R. MEADOWS.

PO Box 397 Hampshire, IL 60140 | (800) 542-POOL | www.deckoseal.com | info@deckoseal.com