

FLOOR-TOP® STG

A standard traffic-grade, single-component, volumetrically-stable, self-leveling floor topping and underlayment that may be pumped or poured.

FLOOR-TOP STG is specially designed to smooth out uneven, rough or minor deteriorated interior concrete floors.



#wrmeadows

P.O. Box 338
Hampshire, IL 60140-0338
Phone: 847/214-2100
Fax: 847/683-4544
www.wrmeadows.com

PRINTED IN USA 5/19-500 #SS-24

FLOOR-TOP STG is ideal for smoothing out and leveling concrete and rigid-based interior substrates prior to the application of a flooring system or coating. **FLOOR-TOP STG** cures to a hard, traffic-wearing surface suitable for foot and light rubber-wheeled traffic. **FLOOR-TOP STG** may be color enhanced with integral colors, dyes, coatings, sealers, or acid stains. The product is designed for residential, commercial, retail, and office applications.

FEATURES/BENEFITS:

- May be applied up to 1" (25.4 mm) thick in a single application.
- Single-component; only requires addition of water.
- May be poured or pumped
- May be pumped using a rotor stator style pump such as the GRACO® ToughTek® MP20 and MP40 Mixing Pumps.
- Specifically designed for fast leveling of floors.
- May be acid stained or dyed.
- May be burnished and further enhanced with BELLATRIX, from W. R. MEADOWS.
- Suitable for engineered wood flooring systems.
- Accepts early foot traffic.
- Floor covering may be installed in as little as 18 hours.
- May be used with radiant heating floor systems.
- Compatible with LIQUI-HARD® ULTRA concrete densifier and chemical hardener from W. R. MEADOWS.

For more information on FLOOR-TOP STG, including guide specifications, usage chart, safety data sheet, and samples, visit www.wrmeadows.com or call (800) 342-5976.



W. R. MEADOWS®

SEALIGHT®

A Family Company Since 1926
QUALITY...SERVICE...INTEGRITY