

HYDRALASTIC™ 836 SL

Cold-Applied, Moisture Cured, Waterproofing Membrane

Self-leveling, cold-applied,
moisture-cure, single-component
waterproofing system.



HYDRALASTIC 836 SL
self-leveling
waterproofing system
is created from a
single-component,
moisture-cured, liquid-
applied compound
that will not shrink
or crack.

follow us:

[@wrmeadows](#)
[facebook.com/wrmeadows](#)
[w-r-meadows-inc](#)
[wrmeadowsinc](#)
[wrmeadowsinc](#)
[#wrmeadows](#)



HYDRALASTIC 836 SL is a cold-applied, low VOC, water catalyst waterproofing system created from a single-component, moisture-cure, liquid-applied compound. The product is designed to self-level on interior, exterior, above- and below-grade horizontal surfaces. It does not shrink, is highly flexible, has a low VOC content, and has a very low odor. It will not crack in extreme cold. **HYDRALASTIC 836 SL** is ideal for positive-side waterproofing for foundations and in between-slab (split slab) applications.

FEATURES/BENEFITS:

- Conforming to ASTM C836
- Skins over in 30 minutes in 75° F (23° C); no dust pick up
- Easy application; self leveling
- Water-catalyzed for faster cure rates
- Will not harm EPS or Styrofoam materials
- Does not freeze; will not be damaged due to freezing weather conditions
- Cures to a tough, flexible membrane

For more information on **HYDRALASTIC 836 SL**,
visit www.wrmeadows.com or call 1-800-342-5976.

