



MasterFormat: 07 13 26

JULY 2022
(Supersedes November 2021)

HYDRASTOP™ SA

Pre-Applied Waterproofing Membrane

DESCRIPTION

HYDRASTOP SA is a composite, self-adhered sheet membrane comprised of a non-woven fabric, elastomeric membrane, and coated release paper. Once concrete is poured against HYDRASTOP SA and the concrete cures, a mechanical bond forms that secures the concrete to the membrane. The HYDRASTOP SA system is comprised of the HYDRASTOP SA membrane as well as MEL-DRAIN™ composite drainage board from W. R. MEADOWS.

USES

HYDRASTOP SA is used as a pre-applied waterproofing membrane in vertical applications where access to the site requires a pre-applied waterproofing membrane prior to pouring the foundation walls. The product can also be used for horizontal suspended balcony slabs that will receive a concrete topping. Compatible substrates include plywood and concrete.

FEATURES/BENEFITS

- Provides a waterproof seal between the membrane and poured concrete wall.
- Helps prevent moisture migration into the structure.

PACKAGING

39" x 50' (991 mm x 15.2 m) long rolls, one roll per carton. Store cartons on pallets and cover if left outside. Keep materials away from sparks and flames.

APPLICATION

Surface Preparation ... Inspect all surfaces for any conditions detrimental to the proper completion of the work. Surfaces should be structurally sound. Remove debris or any other foreign material that could damage the membrane.

Application Method ... HYDRASTOP SA may be applied at temperatures down to 40° F (5° C). MEL-PRIME™ from W. R. MEADOWS should be used to enhance the bond at the selvage edge when conditions warrant it. In colder temperatures, use HYDRASTOP SA LOW TEMP, which can be applied at temperatures down to -7° C (19° F).

Membrane Application ... Mechanically attach with fasteners every 12" (304.8 mm) across the top, within ½" (13 mm) of the top edge of the membrane. Install the membrane with the fabric side facing toward the concrete pour. Remove release paper and roll press onto MEL-DRAIN drainage board.

Prior to application of the blindside membrane, attach MEL-DRAIN™ rolled matrix drainage system from W. R. MEADOWS to lagging or soil retention system.

Remove release paper on 3" (76.1 mm) overlap. Apply membrane and roll press into place with a tile type roller.

End Laps ... Overlap membrane 6" (152.4 mm). Prior to overlap, apply BEM, HYDRALASTIC 836, or MEL-ROL® LIQUID MEMBRANE (two-component) from W. R. MEADOWS in area to be lapped. Roll press membrane into BEM, HYDRALASTIC 836, or MEL-ROL LIQUID MEMBRANE. At terminations of membrane, apply BEM, HYDRALASTIC 836, or MEL-ROL LIQUID MEMBRANE 12" (304.8 mm) wide centered over the termination and while still wet, embed 12" (304.8 mm) wide DETAIL FABRIC into the HYDRALASTIC 836 or MEL-ROL LIQUID MEMBRANE and roll press into place. Ensure that DETAIL FABRIC is centered over the termination with 6" (152.4 mm) on each side of lap edge. Apply additional HYDRALASTIC 836 on all terminations of DETAIL FABRIC.

Penetrations and Protrusions ... Detail around all penetrations using BEM, HYDRALASTIC 836, or MEL-ROL LIQUID MEMBRANE (two-component). Apply BEM, HYDRALASTIC 836, or MEL-ROL LIQUID MEMBRANE by forming a fillet around the pipe or protrusion, overlapping the fabric side of HYDRASTOP SA and the protrusion a minimum of 2.5" (64 mm). If the gap between the protrusion and the membrane is greater than ½" (13 mm), apply DETAIL FABRIC over the fully-cured BEM, HYDRALASTIC 836, or MEL-ROL LIQUID MEMBRANE (minimum 24 hours cure required). All penetration and protrusion surfaces must be clean, rust-free, and sound prior to application of MEL-ROL LIQUID MEMBRANE.

CONTINUED ON REVERSE SIDE ...

W. R. MEADOWS, INC.

P.O. Box 338 • HAMPSHIRE, IL 60140-0338
Phone: 847/214-2100 • Fax: 847/683-4544
1-800-342-5976
www.wrmeadows.com • info@wrmeadows.com

HAMPSHIRE, IL / CARTERSVILLE, GA / YORK, PA
FORT WORTH, TX / BENICIA, CA / POMONA, CA
GOODYEAR, AZ / MILTON, ON / SHERWOOD PARK, AB

Patching ... Prior to pouring, inspect membrane for punctures or damage and repair as necessary with HYDRALASTIC 836 and/or DETAIL FABRIC.

PRECAUTIONS

Concrete should be poured within 60 days of membrane installation. For installations below 40° F (4° C), contact W. R. MEADOWS technical services. When using bar supports, use those with a flat bottom. The use of HYDRASTOP SA does not negate the need for relief of hydrostatic head. A complete drain tile system should be placed around the exterior of footing and under slabs, as required.

For most recent data sheet, further LEED information, and SDS, visit www.wrmeadows.com.

TECHNICAL DATA

Property	Test Method	HYDRASTOP SA Results
Color		White
Thickness	ASTM D1000	80 Mils (Nominally)
Low Temp Flexibility	ASTM D1970, 180° @ -25° F (-32° C)	Pass
Resistance to Hydrostatic Head	ASTM D5385-93	230' (70 m)
Elongation	ASTM D412-06	> 400%
Crack Cycling	ASTM C836 @ -15° F (-26° C)	Pass
Puncture Resistance	ASTM E154	260 lb. (1155 N)
Peel Adhesion to Concrete	ASTM D903	10 lb./in (1754 N/m)



LIMITED WARRANTY

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

Disclaimer

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As W. R. MEADOWS, INC. has no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.