

# SAFETY DATA SHEET

Page 1 of 3

**SECTION 1: PRODUCT AND COMPANY IDENTIFICATION** 

Product: PENCURE™ OTC Part Number: 3548000

Manufacturer: W. R. MEADOWS, INC. Address: 300 Industrial Drive

Hampshire, Illinois 60140

**Telephone:** (847) 214-2100 In case of emergency, dial (800) 424-9300 (CHEMTREC)

Revision Date: 10/4/2019

Product Use: Acrylic Curing Compound

## **SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS**

HMIS		HAZARD STATEMENTS	
Health	1	DANGER!	
Flammability	3	Highly flammable liquid and vapor.	
Reactivity	[0]	Harmful if Inhaled. Causes skin/eye/respiratory irritation.	
Personal Protection		Prolonged/repeated exposure may cause organ damage.	
		May be fatal if ingested and enters airways.	
		PRECAUTIONARY STATEMENTS	
		Keep containers closed when not in use/avoid ignition sources.	
		Avoid breathing vapors and direct contact.	
		Store in well-ventilated location.	
		Wear appropriate Personal Protective Equipment.	

SECTION 3: HAZARDS COMPONENTS						
		% by	SARA	Vapor Pressure	LEL	
Chemical Name:	<b>CAS Number</b>	Weight	<u>313</u>	(mm Hg@20°C)	<u>(@25°C)</u>	
1. Acetone	67-64-1	5-10	No	24 kPa	2.6	
2. Proprietary Solvent Blend	N/E	40-50	No	N/E	N/E	
3. Organic Silane	35435-21-3	15-20	No	23 hPa	0.4	
				N/	F = Not Establish	ed

Use only outdoors or in well-ventilated areas.

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA)

and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."

## **SECTION 4: EMERGENCY AND FIRST AID PROCEDURES**

**EYE CONTACT:** If irritation or redness develops, move victim from exposure source and into fresh air. Flush eyes with water for fifteen (15) minutes. If symptoms persist, seek medical attention.

**SKIN CONTACT:** Wash affected areas with mild soap and water; remove contaminated shoes/clothing. If symptoms persist, seek medical attention.

**INHALATION:** If respiratory symptoms develop, move victim from exposure source and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel.

**INGESTION:** Dilute with liquid unless the victim is unconscious or very drowsy. Do not induce vomiting. If vomiting spontaneously occurs, prevent lung aspiration. Seek immediate medical attention.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND CHRONIC: See Section Eleven for Symptoms/Effects.

## SECTION 5: FIRE AND EXPLOSIVES HAZARDS

FLASHPOINT: -4 °F (For Acetone)

**EXTINGUISHING MEDIA:** Water fog, foam, dry chemical, or carbon dioxide.

CHEMICAL/COMBUSTION HAZARDS: Carbon monoxide, carbon dioxide, and incomplete combustion products.

PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: Avoid smoke inhalation. Personal protective equipment should include helmet, face shield, bunker coat, gloves, rubber boots, and a positive-pressure NIOSH-approved self-contained breathing apparatus. As a result of hydrolysis, flammable vapors may accumulate in container headspace. Consider possible formation of explosive mixtures with air. For example, in uncleaned containers contaminated with moisture. Explosion limits for hydrolysis

product 3.5-15% v/v (ethanol).

## **SAFETY DATA SHEET**

Date of Preparation: 10/4/19 Page 2 of 3 3548000

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

**SPILL OR LEAK PROCEDURES:** Avoid direct contact. Dike and contain spilled material. Remove source of spill if safe to do so. Evacuated all non-essential personnel from immediate area. Remove/extinguish ignition sources. A vapor-suppressing foam may be used to reduce vapor generation. Absorb with non-combustible absorbent and place in sealed containers for disposal. Control run-off and prevent from entering waterways, sewers, etc... Use non-sparking tools to collect spilled material as well as contaminated absorbent.

#### **SECTION 7: HANDLING AND STORAGE**

**SAFE HANDLING PROCEDURES:** Avoid direct contact. Use adequate grounding when decanting. **SAFE STORAGE:** Keep containers closed when not in use. Keep away from ignition sources.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
OSHA

	OSHA				ACGIH			
<u>Chemical Name</u> :	<u>PEL</u>	PEL/CEILING	PEL/STEL	<u>SKIN</u>	<u>TWA</u>	TLV/CEILING	TLV/STEL	<u>SKIN</u>
1. Acetone	1000 ppm	N/E	N/E	Yes	500 ppm	N/E	750 ppm	Yes
2. Proprietary Solvent Blend	N/E	N/E	N/E	N/E	N	N/E	N/E	N/E
3. Organic Silane	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E
								_

**ENGINEERING CONTROLS:** Use with adequate ventilation. Use explosion-proof equipment.

N/E: Not Established

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses, chemical-resistant gloves.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES** 

BOILING POINT: N/E VAPOR DENSITY: >1 (Air=1) % VOLATILE BY VOLUME: N/E

EVAPORATION RATE: <1 (Ether=1) pH LEVEL: N/A % VOLATILE BY WEIGHT: 77 (Approximate)

WEIGHT PER GALLON: 7.83 PRODUCT APPEARANCE: Clear Liquid VOC CONTENT: 331 g/L

ODOR: Mild Organic ODOR THRESHOLD: N/D MELTING/FREEZING POINT: N/D

FLASH POINT: See Section 5 FLAMMABILITY: N/D UEL/LEL: N/D VAPOR PRESSURE: N/D RELATIVE DENSITY: N/D SOLUBILITY: N/D

PARTITION COEFFICENT: N/D AUTOIGNITION TEMPERATURE: N/D DECOMPOSITION TEMPERATURE: N/D VISCOSITY: N/D: Not Determined

SECTION 10: STABILITY/REACTIVITY

STABILITY: Stable. HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS AND MATERIALS TO AVOID: Static discharge, heat, sparks, open flame, and strong oxidizing agents, moisture, acids

and bases.

HAZARDOUS DECOMPOSITION PRODUCTS: Ethanol, carbon monoxide/dioxide, incomplete combustion products.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

EYE CONTACT: Direct contact may cause mild to moderate irritation. Product vapors may also cause irritation.

**SKIN CONTACT:** Direct contact may cause mild skin irritation. Prolonged/repeated contact may result in irritation/dermatitis. **INHALATION:** Exposure may produce irritation to the nose, throat, respiratory tract, and other mucous membranes. Exposure to excessive vapor concentrations may cause signs of transient central nervous system depression (headache, drowsiness, loss of coordination, and fatigue). Repeated/prolonged occupational overexposures may result in permanent damage and can be potentially fatal.

**INGESTION:** This product is anticipated to be slightly toxic. If ingested and lung aspiration occurs serious lung damage may result. Ingestion of excessive quantities may result in symptoms of central nervous system depression.

**SIGNS AND SYMPTOMS:** Symptoms of eye irritation include tearing, reddening, and swelling. Symptoms of skin irritation include reddening, swelling, rash, and redness. Symptoms of gastrointestinal irritation include abdominal pain, vomiting and diarrhea. Sumptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, reduced lung function, and symptoms of central nervous system depression.

**AGGRAVATED MEDICAL CONDITIONS:** Pre-existing skin, lung, liver, kidney, male reproductive, immune/auditory and central nervous system disorders may be aggravated by product exposure.

**OTHER HEALTH EFFECTS:** Prolonged/repeated exposure may affect the central nervous system. Target organs include the liver, kidneys, and adrenal glands. Cardiac sensitization, immune system, and blood abnormalities have been demonstrated in laboratory animals. The relevance to humans is uncertain.

I	SECTION 12: ECOLOGICAL INFORMATION					
Ī	ECOTOXICITY: N/E	DEGRADABILITY: N/E	BIOACCUMULATIVE POTENTIAL: N/E			
ı	SOIL MOBILITY: N/E	OTHER ADVERSE EFFECTS: None recognized.				

**SAFETY DATA SHEET** 

Date of Preparation: 10/4/19 Page 3 of 3 3548000

**SECTION 13: WASTE DISPOSAL INFORMATION** 

WASTE DISPOSAL INFORMATION: Product is considered a hazardous waste for disposal purposes. Appropriate for fuel

blending/incineration.

**SECTION 14: TRANSPORTATION INFORMATION** 

HAZARDOUS/NON-HAZARDOUS MATERIAL: Hazardous.

UN NUMBER: 1866 HAZARD CLASS: 3 PACKING GROUP: ||

UN PROPER SHIPPING NAME: Resin Solution.

ENVIRONMENTAL HAZARDS: Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

BULK TRANSPORTATION INFORMATION: Not applicable. Product not shipped in bulk configuration.

**SPECIAL PRECAUTIONS:** Keep containers closed. Avoid ignition sources.

**SECTION 15: REGULATORY INFORMATION** 

OTHER REGULATORY CONSIDERATIONS: None recognized.

**SECTION 16: OTHER INFORMATION** 

PREPARATION DATE: 10/4/2019
PREPARED BY: Dave Carey

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.