



MasterFormat:  
03 05 00

JANUARY 2022  
(Supersedes December 2008)

## VOCOMP<sup>®</sup>-30

### Water-Based, Acrylic, Concrete Curing and Sealing Compound for Fresh Concrete

#### DESCRIPTION

VOCOMP-30 is a ready-to-use, 30% solids concrete curing and sealing compound formulated of special acrylic polymers in a true water-based carrier. VOCOMP-30 provides improved resistance to rain, sun, petroleum, deicing salts, cleaning agents (except aromatic solvents), diluted caustics, and other pollutants.

Color-wise, VOCOMP-30 appears milky white in the container and, when first applied, leaves a bluish cast on the concrete for easy visual coverage. VOCOMP-30 dries clear to provide a transparent sheen finish.

This product is designed for fresh concrete only.

#### USES

VOCOMP-30 may be used wherever a thicker film, with a medium-to-high sheen, is desired to bring out the natural beauty of concrete without discoloring, checking, or peeling. When properly applied, VOCOMP-30 provides a premium-grade seal for superior moisture protection. It may be applied to simultaneously cure, seal, and dustproof new interior, exterior, horizontal, and vertical concrete surfaces. VOCOMP-30 is ideal for curing, sealing, and dustproofing driveways, sidewalks, patios, swimming pool areas, and commercial and industrial floors. Horizontal surfaces protected with VOCOMP-30 offer excellent wearing qualities for foot and vehicular traffic. If, after prolonged usage, traffic patterns appear, the surface can be washed clean and recoated to restore the original beauty. Good concrete and good concreting practices should be used, as VOCOMP-30 is not a cure-all for improperly mixed or placed concrete.

#### SPECIFICATIONS

- AASHTO M 148, Type 1 or Type 2, Class A & B
- ASTM C 309, Type 1 or Type 2, Class A & B
- ASTM C 1315, Type I, Class A
- Complies with all current federal, state, and local maximum allowable VOC requirements, including U.S. EPA, SCAQMD, and OTC.
- Dried film is USDA accepted.

#### FEATURES/BENEFITS

- Permeable film allows moisture in cured concrete to evaporate.
- Provides a ready-to-use, non-yellowing, water-based compound that seals and protects concrete in one quick and easy application.
- Dries quickly on new concrete to provide a clear, tough, easy-to-clean sheen finish.
- Applicable for use on new interior, exterior, horizontal, and vertical concrete surfaces.
- Offers improved resistance to most chemicals, petroleum, abrasives, and mortar droppings.
- Application tools can be cleaned with soap and water.
- VOC compliant.

#### PACKAGING

1 Gallon (3.79 Liter) Units (4 per case)  
5 Gallon (18.93 Liter) Pails  
55 Gallon (208.20 Liter) Drums

#### SHELF LIFE

When stored indoors in original, unopened containers at temperatures between 40° - 90° F (4° - 32° C), optimum performance and best use is obtained within one year of date of manufacture.

#### TECHNICAL DATA

VOC Content: 157 g/L

**CONTINUED ON REVERSE SIDE ...**

#### W. R. MEADOWS, INC.

P.O. Box 338 • HAMPSHIRE, IL 60140-0338  
Phone: 847/214-2100 • Fax: 847/683-4544  
1-800-342-5976  
www.wrmeadows.com • info@wrmeadows.com

HAMPSHIRE, IL / CARTERSVILLE, GA / YORK, PA  
FORT WORTH, TX / BENICIA, CA / POMONA, CA  
GOODYEAR, AZ / MILTON, ON / SHERWOOD PARK, AB

## APPLICATION

**Surface Preparation ...** Apply VOCOMP-30 when the surface water has disappeared and the concrete surface will not be marred by walking workmen.

**Mixing ...** For optimum performance, gentle mixing or agitation is recommended. CAUTION: TO AVOID FOAMING, DO NOT MIX EXCESSIVELY.

**Application Method ...** A typical industrial sprayer, such as a Chapin 1949, provides an easy, economical method of application. VOCOMP-30 can also be applied using a lint-free roller or lambs wool applicator. Care should be taken to maintain a wet-edge during application to prevent roller marks in dried film.

VOCOMP-30 should be sprayed on with a Chapin 5916 nozzle that produces a flow of 0.1 GPM (0.379 LPM). Spray on in a fine, fog pattern without spurts and dribbles to form a thin, continuous film. AVOID PUDDLING in low areas. If puddles occur, brush or roll them out. For added protection and a greater sheen on new or existing (old) concrete, we recommend two coats of VOCOMP-30 be applied at right angles. Additional coats of VOCOMP-30 may be applied after the first coat has thoroughly dried. Use of improper spray tip or application method may result in a "spotty" appearance.

**Drying Time ...** VOCOMP-30 dries quickly. Drying times may be extended depending on application rate, temperature, humidity, and project conditions. Restrict foot traffic for at least four hours. Twelve hours is preferable.

**Cleanup ...** While VOCOMP-30 is still wet, equipment may be cleaned with soap and water. Once dried, the material may be removed with a solvent such as xylene or toluene.

## PRECAUTIONS

KEEP FROM FREEZING. Do not dilute. Do not apply VOCOMP-30 when air, material, and surface temperatures are expected to fall below 40° F (4° C) within four hours of completed application. DO NOT MIX WATER-BASED COMPOUNDS WITH ANY COMPOUND CONTAINING SOLVENT. VOCOMP-30 may be applied to colored concrete, but mottling may occur.

Concrete floors properly cured with VOCOMP-30 meet the requirements of ASTM C1315: Section 8.8 Adhesion. For any alternate specifications or requirements, secure the approval of the manufacturer of any paint, coating, carpet, adhesive, resilient flooring, floor topping, etc. (any type/composition of subsequent floor treatment) that will be applied over VOCOMP-30. Obtain this approval BEFORE applying their product over concrete previously cured with VOCOMP-30.

VOCOMP-30 can be used on commercial and industrial floors that do not receive heavy forklift traffic. If the floor is going to receive heavy forklift traffic, consider using MED-CURE™ from W. R. MEADOWS as the curing compound, followed by an application of LIQUI-HARD® or LIQUI-HARD ULTRA from W. R. MEADOWS.

## HEALTH AND SAFETY

Direct contact may result in mild irritation. Inhalation may cause irritation of the respiratory tract. Refer to Safety Data Sheet for complete health and safety information.

**For most recent data sheet, further LEED information, and SDS, visit [www.wrmeadows.com](http://www.wrmeadows.com).**



### LIMITED WARRANTY

W. R. MEADOWS, INC. warrants at the time and place we make shipment, our material will be of good quality and will conform with our published specifications in force on the date of acceptance of the order. Read complete warranty. Copy furnished upon request.

### Disclaimer

The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. W. R. MEADOWS, INC. cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As W. R. MEADOWS, INC. has no control

over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.